STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

	7	
POLTUBIATEIO		
SANTA FE	V	
FILE	1	
U.S.G.S.		
LAND OFFICE		<u> </u>
OPERATOR		

OIL CONSERVATION DIVISION

Form	C-1	03	•
Revis	e d	10-	1 - 75

DISTRIBUTION	P. O. BO	OX 2088	Revised 10-1-79
SANTA FE	SANTA FE, NEW MEXICO 87501		API #30-005-62642
FILE V		•	Sa. Indicate Type of Lease
U.S.G.S.			State XX Fee
LAND OFFICE	•		5. State Otl & Gus Leuse No.
OPERATOR			LG 4920
			THIRITINI THE
SUNDRY	NOTICES AND REPORTS O	N WELLS BACK TO A DIFFERENT RESERVOIR.	
USE "APPLICATION	JOH PEHMIT -" (FORM C-101) FOR S	UCH PROPOSALS.)	7. Unit Agreement Name
1.		SECENTED	
OIL WELL XX	OTHER-	RECEIVED	8. Furm or Lease Name
2. Name of Operator			Ibis XU State Com
Yates Petroleum Corporat	ion√		
J. Address of Operator	,	NOV 21 '88	9. Well No.
105 South 4th St., Artes	ia, NM 88210		3
1. Location of Well		0, 0, 0,	10. Field and Poul, or Wildcat
2 16	S50 North	LINE AND ARTES 80 DEFICE	Undes. Orodivician
UNIT LETYER G LD	FEET FROM THE TIOTELL	LINE AND	
Foot	25 99	HANGE 26E NM	
THE LINE, SECTION_	25 TOWNSHIP 9S	RANGENM	
mmmmmm.	15. Elevation (Show wheth	er DF, RT, GR, etc.)	12. County
	3813.		Chaves
	77777		
-		Nature of Notice, Report or	Uther Data
NOTICE OF INT	ENTION TO:	SUBSEQUE	ENT REPORT OF:
·	ـــر		
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON		COMMENCE DRILLING OPHS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING	CHANGE PLANS	CASING TEST AND CEMENT JOB	
		OTHER Production Ca	sing, Perforate, Treat XX
OTHER]	
17. Describe Proposed or Completed Open	ations (Clearly state all pertinent of	letails, and give pertinent dates, includ	ling estimated date of starting any proposed
work) SEE RULE 1103.			
TD 6232'. Ran 149 joi	ints 5-1/2" J-55 15.5#	casing set 6232'. Regu	ılar guide shoe set
62321, float collar se	et 6190'. DV tool set	2212'. Cemented w/350 s	sx 65/35 Poz "C" with
5#/sx salt4% Halad-	-4 and 3% CFR-3. PD 6	:30 AM 11-3-88. Tailed	in w/360 sx Class "C"
with 6#/sx salt and .2	2% CFR-3. PD 11:30 AM	11-3-88. Bumped plug t	to 1000 psi for 30 mins,
released pressure, hel	ld okav. Cement circu	lated.	
Drilled out DV tool at	t 2212'. Continued to	bottom. Circulated hol	le with 10# brine.
Perforated 5910-5972'	w/30.50" holes as fo	11ows: 5910, 11, 12, 13	, 14, 23, 24, 25, 26, 27,
28 20 30 35 36 37	7 38 39 48 49 50	59, 60, 61, 66, 67, 68	70, 71, and 5972'.
20, 29, 30, 33, 30, 37	5010-721 (30 holes) w	tith 1500 gals 15% NEFE a	acid and ball sealers.
Acidized perioracions	3910-72 (30 Notes) w	Tell 1900 Bats 1910 Mara	
			•
	•	•	
	•		
•			
18. I hereby certify that the information at	bove is true and complete to the be	at of my knowledge and belief.	
\cap 0			
	11/2	Production Supervisor	DATE 11-15-88
TION TO THE TOTAL TO THE TOTAL			
Ori	iginal Sipned By		NOV 2 - 1985
	Mika Williams Tirre		DATE