STATE OF NEW MEXICO				1999 - 1999 - 1999 - 1999 - 1999 - 1999 - 1999 - 1999 - 1999 - 1999 - 1999 - 1999 - 1999 - 1999 - 1999 - 1999 -		
ENERGY AND MINERALS DEPARTMENT			TION	LECENEN		
			TION DI	1STON-		
		P. O. BOX 2088				Form C-103 Revised 10-1-1
FILE	SANTA	FE, NEW	MEXICO B	7501		Refised IV-1-1
U.S.G.S.			· •	VDV 14'88	Sa. Indicate Type	of Lease
LAND OFFICE					State	Fee X
OPERATOR			• :		5. State Oll & Ga	
				0. C. D.	3, 31018 ON 8 Gd	a Lease No.
				RTESIA, OFFICE	- Kerrerere	•
SUNDRY NOTICES AND REPORTS ON WELLS 100 NOT USE THIS FOR FOR POPOSALS TO DAILL OR TO OCCUPEN ON PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT (FORM C-101) FOR SUCH PHOPOSALS.)						
1.					7. Unit Agreement tigme	
OIL X GAS WELL	OTHER-				, one representation	TIGHE
2. Name of Operator					8. Farm or Lease liame	
Slash Four Enterprises, Inc.					Toltec	
3. Address of Operator					9. Well No.	
P. O. Box 1433, Roswell, N. M. 88201					1	
4. Location of Well					10, Field and Pool, or Wildcat	
0 33	O	South	23	10	Und. Dial	•
UNIT LETTER +	FEET FROM THE		LINE AND	FEET F40M	mmmm	TTTTTTTTTTT
. Fast	22	105		27E	((((((((((((((((((((((((((((((((((((
THEEast LINE, SECTION	TOWNS	HIP		2711 NMPM.		
mmmmmmmm					12. County	<u>MANNIN </u>
15. Elevation (Show whether DF, RT, GR, etc.) 3838 G.L.						
	111 2020 (Jalua	• ••••••••••••••••••••••••••••••••••••		Chaves	ΔΠΠΠΠ
Check App	propriate Box To	Indicate Na	ture of Noti	ce, Report or Otl	ier Data	
NOTICE OF INTE		1		-	REPORT OF:	
PERFORM REMEDIAL WORK	PLUG AND		REMEDIAL WORK			
TEMPORARILY ABANDON			COMMENCE DRIL			
· F1		r1		100	PLUG AN	D ABANDONMENT
PULL ON ALTER CASING	CHANGE PL		CASING TEST AN	D CEMENT JON [21]		1
			OTHER			L.J
OTHER	<u>**</u> *	[]				
 Describe Proposed or Completed Operat work) SEE RULE 1103. 	tions (Clearly state all	pertinent detail	ls, and give per	tinent dates, including	estimated date of st	arting any proposed
			0 1000	•	a. a. (a.:.'	
				. Set 5' of 1		
				/4" hole to 43		
very little	water. Ran 42	26' of 8 5	5/8" 23# 、	J -55 casi ng wi	th 2 central	lizers,
an insert fl	oat and a Tev	e Pattor	n autida el	Log Comparted	anding with	250

an insert float and a Texas Pattern guide shoe. Cemented casing with 250 sacks of Halliburton "Premium Plus" cement with 2% CaCl. Circulated 16 sacks of cement to pit. Pumped plug to insert float and pressured casing to 600 psi and held pressure 30 minutes, pressure held. W.O.C. 18 hours.

.

.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.							
	الم	President, Slash Four Ent.	DATE <u>11/11/88</u>				
PROVED BY	Original Signed By Mike Williams		NOV 1 5 1988				

- . ..