

JR we need To witness
the cementing thru the
injection zone on this well

100' below. to 100' Above
minium requirements

Should Go to TOC @ ± 5800
+ bring cement up, but
not a necessity

IT IS THEREFORE ORDERED THAT: Order No. R-9432 2/1/91

(1) The applicant, Stevens Operating Corporation, is hereby authorized to utilize its O'Brian "C" Well No. 9 located 1870 feet from the North line and 80 feet from the West line (Unit E) of Section 1, Township 9 South, Range 28 East, NMPM, Chaves County, New Mexico, to dispose of produced salt water into the Devonian formation, Twin Lakes-Devonian Pool, injection to be accomplished through 2 3/8-inch tubing installed in a packer located at approximately 7160 feet, with injection into the perforated intervals from approximately 7211 feet to 7405 feet (7211 feet to 7245 feet and 7392 feet to 7405 feet).

~~Confidential~~
101.5-3-89

2-3-89
Comp. neutron
Litho density
0-7405
Dual lateral log
Micro-SFL
2500-7464

NSL R-8830
APPR. 12-23-88

Smead
No. 2-153C
HASTINGS, MN
LOS ANGELES-CHICAGO-LOGAN, OH
MCGREGOR, TX-LOOCUST GROVE, GA
U.S.A.

NC Tops DOM 2/22/89

Yates	784
7 Rivers	982
San Andres	1922
Glorieta	3105
Yeso	3182
Albo	5375
Wolfcamp	6123
Penn	6620
Miss	6970
Devonian	7212