## STATE OF NEW MEXICO NERGY AND MINERALS DEPARTMENT

(		
DISTRIBUTION		1
BANTA FE	V	
FILE	V	V
U.1.0.1.		
LAHO OFFICE		$X_{-}$
OPERATOR	V	

## OIL CONSERVATION DIVISION

DISTRIBUTE				Form C-103 - Revised 10-1-78	
11/4/ 1/6		SANTA FE, NEW	/ MEXICO 87501	NCT13Ed 10-1-76	
U.S.O.1.				Sa. Indicate Type of Leuse	
LAND OFFICE				State Fee X	
OPERATOR				5. State Off & Gan Leaso No.	
	SUNDRY NOTICES	AND REPORTS ON	WELLS		
(00 40) 010	USE "APPLICATION FOR PERMIT	-" (FORM C-101) FOR SU	WELLS CHEPOPOSALES RECEIVED		
**************************************	WELL OTHER-			7. Unit Agreement Name	
tevens One	erating Corporat	:	1111 20 100	8. Form or Lease Name	
ddress of Operator		.ton·	JUL 26 '89	O'Brien "C"	
. O. Box 2	2408, Roswell, N	ew Mexico 882	201 O. C. D.	9	
ocation of Well			ARTESIA, OFFICE	10. Mold tong Pool, gr Bittaga	
	E . 1870 rec	CT PROM THE North		Siluro-Devonian	
THE West	_		outh mance 28 East		
mmm	a commission	Elevation (Show whether	DF. RT. GR. etc.)	12. County	
		_	4 62	Chaves	
	Check Appropriate	Box To Indicate	Nature of Notice, Report		
N	OTICE OF INTENTION		•	QUENT REPORT OF:	
SFORM REMEDIAL WO	AK	PLUG AND ABANDON	ACMEDIAL WORK	ALTERING CASING	
PORARILY ABANDON			COMMENCE DRILLING OPHS.	PLUG AND ABANDONMENT	
DHIBAD RETLA RO J.		CHANGE PLANS	CASING TEST AND CEMENT JOS	×	
OTHER					
Describe Proposed	or Completed Operations (Cleans to 103.	arly state all pertinent de	tails, and give pertinent dates, in	cluding estimated date of starting any proposed	
6-21-89	Perforated 7403'-	-7405', 2 shots	ner foot		
	Perforated 7403'-7405', 2 shots per foot. Perforated 7392'-7396', 2 shots per foot.				
·	Set CIBP @ 3380'. Perforated 3300'-3302', 2 shots per foot with casing loaded				
	with water. Pres	ssured up on cas	sing and circulated w	ell.	
6-22-89	Pumped 200 sacks	of 25/65 Dom A			
0 22 0)	Pumped 200 sacks of 35/65 Poz A with 6% D20 with 1/4 lb. of flakes. Tailed with 100 sacks class C cement with 1/4 lb. flakes. Displaced down casing with				
	77 Bbls of water.		ith 1/4 lb. Hakes.	Displaced down casing with	
( 0( 00	_				
6-26-89	Ran cement bond log. Top of cement at 1030'. Pressured backside to 750#, held OK.				
	neid OK.				
6-27-89	Set packer at 7150', treated with 5000 gallons acid, flushed with 150 Bbls treated water.				
6 20 00	D 11 1	•			
6-28-89	Pulled packer. On	1 pump 4:00pm 6-	-28-89.		
I hereby certify the	at the information above is true	and complete to the bes	t of my knowledge and belief.		
72P,	L		oduation Comment		
****	June	TITLE PE	oduction Superintend	ent_ DATE	
	ORIGINAL SIGNED	9 54			
40V(D 84	MING WILLIAMS	POINT IL TITLE		JUL 2 7 1989	

SUPERVISOR, DISTRICT IF

PHOLYTONE OF APPROVAL, IF ANYL