Submit 3 Copies to Appropriate District Office

CONDITIONS OF APPROVAL, IF ANY:

State of New Mexico inergy, erals and Natural Resources Department

	/	_
	$\cdot \nu^-$	1
Form C-103	۱ ۱,	ı
LOLLI C-100 O	•	
Revised 1-1-89		
Kealaed 1-1-92	\0	
	UX	
	٠,	

Dadw Cilar				
DISTRICT I P.O. Box 1980, Hobbs, NM 88240	OIL CONSERVATION DIVISION P.O. Box 2088		WELL API NO.	
Comp. Nov. Marica 97504 2099		30-005-62667		
DISTRICT II Santa Fe, New Mexico 6/304-2066 P.O. Drawer DD, Artesia, NM 88210		5. Indicate Type of Lease STATE FEE FEE		
DISTRICT III 1000 Rio Brazos Rd., Aziec, NM 87410			6. State Oil & Gas Lease No.	
			15349	
(DO NOT USE THIS FORM FOR PI	TICES AND REPORTS ON WEL ROPOSALS TO DRILL OR TO DEEPEN ERVOIR. USE "APPLICATION FOR PER C-101) FOR SUCH PROPOSALS.)	COENCE DISCHARGE TO A	7. Lease Name or Unit Agreement Name	
1. Type of Well: OIL GAS WELL WELL	X / OTHER	FEB 24 '89	S.E. State	
2. Name of Operator		O. C. D.	8. Well No.	
ELK OIL COMPANY	/	RTESIA, OFFICE	3	
3. Address of Operator		,	9. Pool name or Wildcat Foor Ranch Pre-Permian	
	swell, New Mexico 88202-0	310	Foor Ranch Fre-Termian	
4. Well Location	1980 Feet From The East	Line and	990 Feet From The South Line	
			Chaves Court	
Section 23	Township 9S Ri	nge 26E	NMPM Chaves County	
	10. Elevation (Show whether		<i>\(\(\(\(\(\(\(\(\)\\\\\\\\\\\\\\\\\\\\</i>	
			Penort or Other Data	
	k Appropriate Box to Indicate	Nature of Monce, i	BSEQUENT REPORT OF:	
NOTICE OF I	NTENTION TO:	501	BSEQUENT REPORT OF	
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING	
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT				
PULL OR ALTER CASING]	CASING TEST AND	CEMENT JOB 🔠	
OTHER:		OTHER:		
10 D 7 D 11 Cived O	tions (Clearly state all pertinent details,	and give pertinent dates, inc	luding estimated date of starting any proposed	
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.				
	a l ll Fahman 2	0 1080 Drill	12¼" hole to 1013'.	
Spud well on February 20, 1989. Drill 12¼" hole to 1013'. Ran 25 joints (1013') of 8 5/8", 23#, ST&C casing. Cemented				
with 325 sxs Hallilite, 5# Salt, 1/4# flocele, 9# gilsonite.				
Tailed with 200 sxs Premium Plus, 4# flocele, 2% CaCl.				
Circulated 50 sxs. WOC 18 hours. Tested to 1000# for				
30 minutes, test okay. Resume drilling a 7 7/8" hole.				
	is true and complete to the best of my knowledge a	nd belief.		
I hereby certify that the information move		Preside	ent	
SIGNATURE		mre		
TYPE OR PRINT NAME			TELEPHONE NO.	
This areas (~ State Hea)			mma a a 1000	
(This space for State Use)	Original Signed By	•	FEB 2 8 1989	
	Mike Williams	mue ————	DATE -	
APPROVED BY				