

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
Artesia, NM 88210
DRAWER DD

Expires August 31, 1985
5. LEASE DESIGNATION AND SERIAL NO.
NM-8431
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐ REVISED
2. NAME OF OPERATOR McClellan Oil Corporation
3. ADDRESS OF OPERATOR P.O. Box 730, Roswell, NM 88201
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface
660 FSL & 1980 FEL
14. PERMIT NO.
15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3755 G.L.
12. COUNTY OR PARISH Chaves
13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	☐	WATER SHUT-OFF	☐
FRACURE TREAT	☐	FRACURE TREATMENT	☐
SHOOT OR ACIDIZE	☐	SHOOTING OR ACIDIZING	☐
REPAIR WELL	☐	REPAIRING WELL	☐
(Other)	☐	(Other)	☐
PULL OR ALTER CASING	☐	ALTERING CASING	☐
MULTIPLE COMPLETE	☐	ABANDONMENT*	☐
ABANDON*	☐	AMENDED cement & casing	☒
CHANGE PLANE	☐	(Note: Report results of multiple completion on Well Completion or Reconpletion Report and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

7/17/89: Move in WEK #3. Spud with 12 1/4" bit. TD at 908 ft. Ran 908 ft, 8 5/8" 23 lb/ft casing. Cemented with 250 sx Pace Setter Lite with 2% CaCl2 and 200 sx Class C with 2% CaCl2. Circulated 68 sacks. WOC- 8 hrs. Nipple up BOP's. Tested to 1700 psi for 30 minutes.

7/18/89: WOC an additional 12 hours.

7/28/89: TD at 4740 ft. Logged with Schlumberger CNL-LDT. Ran 4687' of 4 1/2", 10.5 lb/ft used casing. Cemented with 275 sx Class C, Poz, "65/35" with 5 lb/sk salt, .3% CFR-3 and .3% Halad-4. Released Rig.

Will attempt completion when rig moves.

18. I hereby certify that the foregoing is true and correct

SIGNED Paul Paydole TITLE Operations Manager DATE 8-29-89

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

