

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

APR 10 '89

WELL API NO. 30-005-62683
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. LG 7421
7. Lease Name or Unit Agreement Name Sunny Side State Unit
8. Well No. 2
9. Pool name or Wildcat Wildcat Ordovician
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3922.5' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter B : 660 Feet From The North Line and 1980 Feet From The East Line Section 1 Township 10S Range 26E NMPM Chaves County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.
Spudded 12 1/4" hole 9:45 AM 4-1-89. Ran 31 joints 8-5/8" 24# J-55 ST&C casing set 1312'. Texas Pattern Notched guide shoe set 1312', insert float set 1274'. Cemented w/450 sx Pacesetter Lite, 1/4#/sx Celloseal, 5#/sx Gilsonite, 3% CaCl2 (yield 1.84, weight 12.7). Tailed in w/150 sx Class "C" + 2% CaCl2 (yield 1.32, weight 14.8). PD 7:30 PM 4-3-89. Bumped plug to 1000 psi, released pressure and float held okay. Circulated 15 sacks. WOC. Drilled out 2:45 PM 4-4-89. NU and tested to 1000 psi for 30 minutes, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 4-7-89
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

Original Signed By
Mike Williams

APPROVED BY _____ TITLE _____ DATE APR 11 1989

CONDITIONS OF APPROVAL, IF ANY:

