

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

Santa Fe	File	☒
BLM		
Land Office		
B of M		
Operator		☒

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO.
30-005-62695

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
LG 6688

7. Lease Name or Unit Agreement Name

Middle Creek State Unit

8. Well No.
1

9. Pool name or Wildcat
Wildcat Abo

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER

RECEIVED

2. Name of Operator
YATES PETROLEUM CORPORATION

JUN 15 '89

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter D : 990 Feet From The North Line and 660 Feet From The West Line

Section 33 Township 8S Range 23E NMPM Chaves County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3912.1' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 17" hole 3:00 PM 5-30-89. Set 36' of 14" conductor. Notified NMOC, Artesia, of spud. Resumed drilling 12 1/2" hole 6:00 PM 6-1-89. Lost circulation at 65'. Caving boulders at 85-95'. Cemented w/7 yds redi-Mix. Ran 20 jts 8-5/8" 24# J-55 ST&C casing set 834'. Guide shoe set 834', insert float set 791'. Cemented w/250 sx Thickset w/10#/sx Gilsonite, 1/2/sx Flocele, 3% CaCl2 (yield 1.45, wt. 14.2). Tail in w/200 sx Cl C + 2% CaCl2 (yield 1.32, wt. 14.8). PD 2:15 AM 6-10-89. Bumped plug to 500 psi, float held OK. Cement did not circulate. WOC 6 hr. Ran temperature survey and found TOC 600'. Ran 1". Tag cement 625'. Spot 50 sx Thixset+ 10#/sx Gilsonite+1/2#/sx Flocele+4% CaCl2. PD 11:00 AM 6-10-89. WOC 1 hr. Ran 1". Tag cement 625'. Spot 50 sx Thixset + 10#/sx Gilsonite + 1/2#/sx Flocele + 4% CaCl2. PD 12:30 PM 6-10-89. WOC 1 1/2 hr. Ran 1". Tag cement 625'. Spot 25 sx Cl C + 4% CaCl2. PD 3:15 PM 5-10-89. WOC 1 hr. Ran 1". Tag cement 535'. Spot 75 sx Cl C + 4% CaCl2. PD 4:45 PM 6-10-89. WOC 1 hr. Ran 1". Tag cement 325'. Spot 100 sx Cl c + 4% CaCl2. PD 6:30 PM 6-10-89. WOC 1 hr. Ran 1". Tag cement 147'. Spot 9 yd Redi-Mix to surface (hole dry to 147'). PD 8:30 PM 6-10-89. WOC. Drilled out 7:00 PM 6-11-89. WOC 40 hr, 45 min. NU and test to 1000 psi for 30 min. Reduced hole to 7-7/8". Drilled plug and resumed drlg.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 6-14-89
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS
SUPERVISOR, DISTRICT IV

APPROVED BY

TITLE

DATE

JUN 16 1989

CONDITIONS OF APPROVAL, IF ANY: