

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Santa Fe	
File	
BLM	
Land Office	
B of M	
Operator	

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-005-62698

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator
YATES PETROLEUM CORPORATION

JUN 15 '89

3. Address of Operator
105 South 4th St., Artesia, NM 88210

C. C. D.
ARTESIA OFFICE

7. Lease Name or Unit Agreement Name

Geneva UI Com

8. Well No.

1

9. Pool name or Wildcat
Undes. Pecos Slope Abo

4. Well Location
Unit Letter C : 660 Feet From The North Line and 1980 Feet From The West Line

Section 20 Township 6S Range 26E NMPM Chaves County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3870.8' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 12:25 PM 6-8-89. Set 40' of 20" conductor. Notified John Robinson, NMOCD, Artesia, NM, of spud.
Resumed drilling 17-1/2" hole 9:45 AM 6-11-89. Ran 15 joints 13-3/8" 54.5# J-55 ST&C R-3 casing set 648'. Guide shoe set 648', insert float set 606'. Cemented w/100 sx Thixset + 10#/sx Gilsonite + 1/2#/sx Flocele + 3% CaCl2, 350 sx Halliburton Lite + 3% CaCl2 + 1/2#/sx Flocele (yield 1.84, wt. 12.7). Tailed in w/200 sx Class C + 2% CaCl2 (yield 1.32, wt. 14.8). PD 5:00 PM 6-12-89. Bumped plug to 500 psi, float held okay. Circulated 100 sx to pit. WOC.

Drilled out 11:00 AM 6-13-89. WOC 18 hrs. Cut off and weld on flow nipple. Reduced hole to 12-1/4". Drilled plug and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 6-14-89

TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS
SUPERVISOR, DISTRICT II

APPROVED BY _____ TITLE _____ DATE JUN 21 1989

CONDITIONS OF APPROVAL, IF ANY: