

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Santa Fe	
File	
BLM	
Land Office	
B of M	
Operator	

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-005-62699
5. Indicate Type of Lease STATE ☐ FEE ☒
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Finley RV Com
8. Well No. 2
9. Pool name or Wildcat Undes. Pecos Slope Abo

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) RECEIVED	
1. Type of Well: OIL WELL ☐ GAS WELL ☒ OTHER	
2. Name of Operator YATES PETROLEUM CORPORATION	JUN 15 '89
3. Address of Operator 105 South 4th St., Artesia, NM 88210	C. C. D. ARTESIA, OFFICE
4. Well Location Unit Letter H : 1980 Feet From The North Line and 660 Feet From The East Line Section 33 Township 6S Range 25E NMPM Chaves County	10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3730.2' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	ALTERING CASING ☐
PULL OR ALTER CASING ☐	COMMENCE DRILLING OPNS. ☒
OTHER: ☐	PLUG AND ABANDONMENT ☐
	CASING TEST AND CEMENT JOB ☒
	OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 12:50 PM 6-5-89. Set 40' of 20" conductor. Resumed drilling 17½" hole 10:00 AM 6-7-89. Lost returns 102'. Ran 15 jts 13-3/8" 54.5# J-55 ST&C casing set 653'. Guide shoe set 653', insert float set 608'. Cemented w/150 sx Cl C w/12% Thickset, 3% CaCl2 and 300 sx Pacesetter Lite C, 1/4#/sx Celloseal, 5#/sx Gilsonite, 3% CaCl2 (yield 1.84, wt. 12.7). Tail in w/200 sx Cl C + 2% CaCl2 (yield 1.32, wt. 14.8). PD 8:00 AM 6-9-89. Bumped plug to 750 psi, float did not hold. Cement did not circulate. WOC 5 hrs. Ran Temperature Survey and found TOC 100'. Ran 1". Tag cement 110'. Spot 50 sx Cl C + 6% CaCl2. PD 2:30 PM 6-9-89. WOC 45 min. Ran 1". Tag cement 105'. Spot 50 sx Cl C + 6% CaCl2. PD 3:15 PM 6-9-89. WOC 1½ hrs. Ran 1". Tag cement 101'. Spot 50 sx Cl C + 6% CaCl2. PD 4:30 PM 6-9-89. WOC 1 hr. Ran 1". Tag cement 95'. Spot 50 sx Cl C + 6% CaCl2. PD 5:30 PM 6-9-89. WOC 1½ hr. Ran 1". Tag cement 93'. Spot 55 sx Cl C + 6% CaCl2. PD 7:00 PM 6-9-89. WOC 1 hr. Ran 1". Tag cement 33'. Spot 110 sx Cl C + 2% CaCl2. PD 8:15 PM 6-9-89. WOC 1 hr. Ran 1". Tag cement 33'. Spot 110 sx Cl C + 2% CaCl2. PD 9:30 PM 6-9-89. Circulated 15 sx to surface. WOC. Drilled out 4:30 AM 6-10-89. WOC 20 hrs and 30 min. Reduced hole to 12½". Drilled plug and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 6-14-89

TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)
ORIGINAL SIGNED BY
M. WILLIAMS
DIRECTOR DISTRICT II

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

JUN 16 1989