

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Santa Fe	
File	
BLM	
Land Office	
B of M	
Operator	

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-005-62699
5. Indicate Type of Lease STATE ☐ FEE ☒
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Finley RV Com
8. Well No. 2
9. Pool name or Wildcat Undes. Pecos Slope Abo

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL ☐ GAS WELL ☒ OTHER ☐	
2. Name of Operator YATES PETROLEUM CORPORATION	
3. Address of Operator 105 South 4th St., Artesia, NM 88210	C. C. D. ARTESIA, OFFICE
4. Well Location Unit Letter <u>H</u> : <u>1980</u> Feet From The <u>North</u> Line and <u>660</u> Feet From The <u>East</u> Line Section <u>33</u> Township <u>6S</u> Range <u>25E</u> NMPM <u>Chaves</u> County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3730.2' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	ALTERING CASING ☐
PULL OR ALTER CASING ☐	COMMENCE DRILLING OPNS. ☐
OTHER: ☐	PLUG AND ABANDONMENT ☐
	CASING TEST AND CEMENT JOB ☐
	OTHER: <u>Intermediate Casing set</u> ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6-11-89. Set cement plugs as follows: #1 - 100 sx C1 C w/12% Thickset, 3% CaCl2, 12#/sx Gilsonite. Tag 961'. PD 5:30 AM 6-11-89. #2 - 100 sx C1 C, 12% Thickset, 3% CaCl2, 12#/sx Gilsonite. PD 8:30 AM 6-11-89. Tag at 900'. #3 - 100 sx C1 C, 12% Thickset, 3% CaCl2, 12#/sx Gilsonite. PD 10:30 AM 6-11-89. Tag at 765'. #4 - 100 sx C1 C, 6% CaCl2, PD 1:45 PM 6-11-89. Tag at 580'. WOC. Began drlg cement 12:15 AM 6-12-89. Ran 36 jts 8-5/8" 24# J-55 ST&C casing set 1505'. Guide shoe set 1505', insert float set 1465'. Cemented w/150 sx C1 C+12% Thixset + 3% CaCl2, 12#/sx Gilsonite (yield 1.50, wt 14.8). Tail in w/200 sx C1 C+2% CaCl2 (yield 1.50, wt 14.8). PD 7:15 AM 6-14-89. Bumped plug to 750 psi, float held okay. Cement did not circulate. WOC 5 hr. Ran Temperature Survey-TOC 1130'. Ran 1". Tag cement 1150'. Spot 30 sx C1 C+4% CaCl2. PD 2:00 PM 6-14-89. WOC 3 1/2 hr. Ran 1". Tag cement 1098'. Spot 50 sx C1 C+4% CaCl2. PD 5:15 PM 6-14-89. WOC 3 1/2 hr. Ran 1". Tag cement 800'. Spot 100 sx C1 C+4% CaCl2. PD 8:45 PM 6-14-89. WOC 4 hr. Ran 1". Tag cement 650'. Spot 200 sx C1 C+4% CaCl2. PD 12:45 AM 6-15-89. WOC 2-3/4 hr. Ran 1". Tag cement 105'. Spot 60 sx C1 C+2% CaCl2. PD 3:30 AM 6-15-89. Circ. 10 sx. WOC. Drill out 12:30 PM 6-15-89. WOC 29 hr, 15 min. NU and tested to 1000# for 30 min, OK.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. Reduced hole to 7-7/8". Drld plug, resumed drlg

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 6-16-89
TYPE OR PRINT NAME: Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY _____ TITLE _____ DATE JUN 21 1989

CONDITIONS OF APPROVAL, IF ANY: