

Submit 3 Copies
to Appropriate
District Office

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

State of New Mexico
Energy, Minerals and Natural Resources Department

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

State	Fe
BLM	
Land Office	
B or M	
Operator	

Form C-103
Revised 1-1-89

WELL API NO.
30-005-62699

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter H : 1980 Feet From The North Line and 660 Feet From The East Line

Section 33 Township 6S Range 25E NMPM Chaves County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3730.2' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Production Csg, Perforate, Treat ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 4100'. Reached TD 7:30 AM 6-19-89. Ran 97 joints 4½" casing as follows: 96 jts 4½"
10.5# J-55 ST&C and 1 jt 9.5# J-55 ST&C casing set 4100'. Regular guide shoe set 4100',
float collar set 4058'. Cemented w/475 sx 65/35 "C" + .7% CF-1 + 1/4/sx Celloseal + 5#/sx
Salt (yield 1.39, wt. 14.2). PD 10:00 AM 6-20-89. Bumped plug to 1800 psi for 10 minutes,
float and casing held OK. WOC 18 hrs. Ran 1" between 8-5/8" and 4½" casing to 1700'. Cemented
w/350 sx Pacesetter cement. Circulated 5 sx to surface. Perforated 3540-3648' and 3862-68'
w/26 - .42" holes as follows: 3540, 41, 45, 46, 49, 61, 62, 99, 3600, 01, 02, 46, 47 and 48'
(14 holes-1 SPF); 3862-68' (12 holes-2 SPF).
Acidize in two stages perforations 3540-3648' and 3862-3868' w/2500 gals 7½% acid.
Frac'd perforations (via 4½" casing) with 60000 gals gel KCL and 110000# 20/40 sand.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 6-30-89

TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY

APPROVED BY JUL 7 1989 TITLE DATE

CONDITIONS OF APPROVAL, IF ANY: