State of New Mexico Submit 3 Copies to Appropriate RECEIVED RECEIVE RECEIV		Santa Fe rije BLM Land Office B of M	Form C-103 Revised 1-1-89
DISTRICT I P.O. Box 1980, Hobbs, NM 88249UN 27 89 CONSERVATION DIVISION P.O. Box 2088  DISTRICT II Santa Fe, New Mexico 87504-2088		WELL API NO. 30-005-62703  5. Indicate Type of Lease	
P.O. Drawer DD, Artesia, NM 88210 C. D.  DISTRICT III 1000 Rio Brazos Rd., Aziec, NM 4874101A, OFFICE		6. State Oil & Gas Lease No. LG 6684	
SUNDRY NOTICES AND REPORTS ON WELLS  ( DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  (FORM C-101) FOR SUCH PROPOSALS.)		7. Lease Name or Unit Agreement Name	
1. Type of Well: OBL GAS WELL X OTHER		Trellis AGP State	
2. Name of Operator YATES PETROLEUM CORPORATION		8. Well No.	
3. Address of Operator 105 South 4th St., Artesia, NM 88210		9 Pool name or Wildcat Undesignated West Pecos Slope Abo	
4. Well Location  Unit Letter I : 1980 Feet From The South	Line 2nd660	Feet From TheE	ast Line
16 m 85 Pe	000	NMPM Chaves	County
Section 10. Elevation (Show whether	DF, RKB, RT, GR, etc.)		
3967.5' GR  Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data			
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:			
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING			NG CASING
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT			ND ABANDONMENT L
PULL OR ALTER CASING CASING TEST AND C		•	
OTHER: OTHER: Production Csg, Per			
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, a work) SEE RULE 1103.			
TD 3500'. Ran 83 joints 4-1/2" 9.5# J-55 ST 3500'. Float collar set 3458'. Marker joi 500 gals Flocheck 21, 450 sx 65/35 Poz C wit 1.41, weight 14.2). PD 7:45 AM 6-15-89. But held okay. Perforated 2937-3074' w/2040 43, 82, 83, 84, 87, 88, 89 and 90' (1 SPF); in three stages w/2250 gals 15% acid. Frac gelled 2% KLC water and 100000# 20/40 sand.	nt set 2851'. h .4% Halad-4, imped plug to 15 " holes as foll 3071-74' (2 SP)	Cemented w/500 ga .3% CFR-3 + 5#/sx 500 psi, released Lows: 2937, 38, 3 F). Acidized per	als mudflush,  k Salt (yield  pressure,  39, 40, 41, 42,  fs 2937-3074'
SIONATURE	d belief. mur. Production S		TE 6-23-89 DEPTHONE NO. 505/748-1471
TYPEOR PRINT NAME Juanita Goodlett		TEL	EPISONE NO. 303/740=147.
(This space for State Use)  ORIGINAL SIGNED BY MIKE WILLIAMS SUPERVISOR, DISTRICT IT T	m.e	DA1	JUN 2 8 1989
COMPRESSION OF ADDOCUMENT TO ANY			