

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

FEB 14 '90

WELL API NO.

30-005-62705

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☒

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION (505) 748-1471

3. Address of Operator

105 South 4th St., Artesia, NM 88210

7. Lease Name or Unit Agreement Name

Geneva UI

8. Well No.

2

9. Pool name or Wildcat

Pecos Slope Abo

4. Well Location

Unit Letter B : 660 Feet From The North Line and 1980 Feet From The East Line

Section 20 Township 6S Range 25E NMPM Chaves County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3871.2' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Production Casing, Perforate, Treat ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 4115'. Reached TD 4:00 AM 1-31-90. Ran 97 joints 4-1/2" 9.5# J-55 ST&C casing set 4115'. Guide shoe set 4115, float collar set 4072'. Cemented w/500 gals Excellogel, 500 gals Surebond, 500 sx 65/35 "C" w/.7% CF-1, 1/2# Celloseal, 5# Hyseal and 5# salt/sx (yield 1.39, wt 14.7). PD 10:15 PM 2-1-90. Bumped plug to 1400 psi for 3 minutes, float and casing held okay. WOC 18 hrs.

Perforated 22 .41" holes 3570-3882' as follows: 3570-76' (7 holes), 3795-98' (4 holes) and 3872-82' (11 holes). Acidized perforations 3580-3882' in three stages w/2700 gals 7 1/2% NEFE acid.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Juanita Goodeltt

TITLE

Production Supervisor

DATE 2-13-90

TYPE OR PRINT NAME

TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY

MIKE WILLIAMS

APPROVED BY

TITLE

DATE

FEB 21 1990

CONDITIONS OF APPROVAL, IF ANY: