

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 208
Santa Fe, New Mexico 87504-2088

FEB 26 '90

WELL API NO. 30-005-62705
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR TO CHANGE TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	7. Lease Name or Unit Agreement Name Geneva UI
2. Name of Operator YATES PETROLEUM CORPORATION / (505) 748-1471	8. Well No. 2
3. Address of Operator 105 South 4th St., Artesia, NM 88210	9. Pool name or Wildcat Pecos Slope Abo
4. Well Location Unit Letter <u>B</u> : <u>660</u> Feet From The <u>North</u> Line and <u>1980</u> Feet From The <u>East</u> Line Section <u>20</u> Township <u>6S</u> Range <u>25E</u> NMPM <u>Chaves</u> County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3871.2' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <u>Production Casing, Perforate, Treat</u> <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 4115'. Reached TD 4:00 AM 1-31-90. Ran 97 joints 4-1/2" 9.5# J-55 ST&C casing set 4115'. Guide shoe set 4115, float collar set 4072'. Cemented w/500 gals Excellogel, 500 gals Surebond, 500 sx 65/35 "C" w/.7% CF-1, 1/2# Celloseal, 5# Hyseal and 5# salt/sx (yield 1.39, wt 14.7). PD 10:15 PM 2-1-90. Bumped plug to 1400 psi for 3 minutes, float and casing held okay. WOC 18 hrs.

Perforated 22 .41" holes 3570-3882' as follows: 3570-76' (7 holes), 3795-98' (4 holes) and 3872-82' (11 holes). Acidized perforations 3570-3882' in three stages w/2700 gals 7 1/2% NEFE acid.

*Correction.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodeltt TITLE Production Supervisor DATE 2-13-90
TYPE OR PRINT NAME Juanita Goodeltt TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS
SUPERVISOR, DISTRICT II

APPROVED BY _____ TITLE _____ DATE MAR 12 1990

CONDITIONS OF APPROVAL, IF ANY: