Submit 3 Copies to Appropriate District Office

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

+	c15/
) () P

DIS	IRIC	LL			
P.O.	Box	1980.	Hobbs.	NM	88240

DISTRICTII P.O. Drawer DD, Artesia, NM 88210

CONDITIONS OF APPROVAL, IF ANY:

OIL CONSE**NCE TION DIVISION**

P.O. Box 2088 Santa Fe, New Mexico 87504-2088

WELL API NO. 30-005-62707	
5. Indicate Type of Lease	ree

1000 Rio Brazos Rd., Aztec, NM 87410 6. State Oil & Gas Lease No. O. C. D. L-6772 SUNDRY NOTICES AND REPORTS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7. Lease Name or Unit As sement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) Whitworth RU State 1. Type of Well: METT X METT ____ OTHER 2. Name of Operator 8. Well No. YATES PETROLEUM CORPORATION ~ 3. Address of Operator 9. Pool name or Wildcat 105 South 4th St., Artesia, NM 88210 Und. Foor Ranch Wolfcamp 4. Well Location 660 Feet From The South __ Line and __1980_ Unit Letter Feet From The East 12 26E Chaves Range Section Township **NMPM** 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3828.3' GR Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PLUG AND ABANDON REMEDIAL WORK ALTERING CASING

PERFORM REMEDIAL WORK TEMPORARILY ABANDON **CHANGE PLANS** COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT **PULL OR ALTER CASING** CASING TEST AND CEMENT JOB OTHER: Production csg, perforate, treat OTHER:

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. TD 5450'. Reached TD 5:00 AM 7-31-89. Ran 130 joints $5\frac{1}{2}$ " 15.5# J-55 ST&C casing set

5450'. Guide shoe set 5450', float collar set 5409'. Cemented w/300 sx 65/35/2"C" + .7% CF-1 + 5#/sx Salt (yield 1.4, wt 13.8). PD 6:45 PM 7-31-89. Bumped plug to 1600 psi for 15 mintues, released pressure, float and casing held okay. Perforated 5342-5349' w/15 .46" holes. Acidized perfs 5342-5349' w/1000 gals 15% NEFE acid. Set retainer at 5325'. Establish pump in and squeeze perfs 5342-5349' w/100 sx (50+50). Squeezed well to 1800 psi with 70 sx in formation. Reversed out 30 sacks. Perforated 5251-5257' w/15 .46" holes. Acidized perfs 5251-5257' w/1500 gals 15% NEFE acid.

	nation above is true and complete to the best of my know	ledge and belief.	
SIGNATURE LUCA	nuta Daviller	TIME Production Supervisor	DATE
TYPE OR PRINT NAME	Juanita Goodlett		ТЕГЕРНОНЕ NO. 505/748-1471
(This space for State Use)	CRISTA COSTALD 87		AUG 2 1 1989
APPROVED BY	- 8872.07053.1.163766711 -	— TITLE	DATE