Submit 3 CopiesState of New MexicoForm C-103to AppropriateEnergy, Minerals and Natural Resources DepartmentRevised 1-1-89District OfficeControl of the second	'₽0 ^T			
	• (
DISTRICT I P.O. Box 1980, Hobbs, NM 88240 DISTRICT II Santa Fe, New Mexico, 87504-2088 Santa Fe, New Mexico, 87504-2088				
P.O. Drawer DD, Artesia, NM 88210 Statte V, New Mickley 075072005 SEP 25 '89 5. Indicate Type of Lease	3			
DISTRICT III 1000 Rio Brazos Rd., Aziec, NM 87410 O, C. D. LG 780				
SUNDRY NOTICES AND REPORTS ON WELLS ARTESIA, OFFICE (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)				
1. Type of Well: OIL OIL River Bridge UX State WELL WELL OTHER	River Bridge UX State			
2. Name of Operator 8. Well No. YATES PETROLEUM CORPORATION 4	8. Well No. 4			
3. Address of Operator9. Pool name or Wildcat105 South 4th St., Artesia, NM 88210Und. South Pecos Slope Abo				
4. Well Location Unit LetterC : Feet From The North Line and Feet From The West Line				
Section 16 Township 9S Range 25E NMPM Chaves Co	unty			
3582.8' GR				
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:				
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:	SUBSEQUENT REPORT OF:			
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING				
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. X PLUG AND ABANDONME	COMMENCE DRILLING OPNS. X PLUG AND ABANDONMENT			
PULL OR ALTER CASING				
OTHER: OTHER:				

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 5:00 PM 9-18-89 with Frank's Rathole Service. Set 40' of 20" conductor. Notified John Robinson, NMOCD, Artesia, NM, of spud. Lost circulation 105'. Pumped LCM pill, regained 80-95% circulation. Resumed drilling 12-1/4" hole 4:30 PM 9-19-89. Notified John Robinson, NMOCD, Artesia, NM. Ran 20 joints 8-5/8" 24# J-55 casing set 863'. Guide shoe set 863', insert float set 820'. Cemented w/350 sx Pacesetter Lite w/10#/sx Hiseal + 1/2#/sx Celloseal + 3% CaCl2 (yield 1.8, wt 12.7). Tailed in w/200 sx Class c + 2% caCl2 (yield 1.32, wt 14.8). PD 11:00 AM 9-21-89. Bumped plug to 750 psi, released pressure and float held okay. Circulated 65 sx to pit. WOC. Drilled out 5:00 AM 9-22-89. WOC 18 hrs. NU and tested to 1000 psi for 30 minutes, held OK. Reduced hole to 7-7/8". Resumed drilling.

- (-)	nation above is true and complete to the best of my knowledge and belief. <u>mTa Daulut</u> production Supervisor	DATE9-22-89
TYPE OR PEINT NAME	Juanita Goodlett	тецерноме NO, 505/748-147
(This space for State Use)	ORIGINAL SIGNED BY MIKE WILVIAMS	SEP 2 6 1989
APPROVED BY	SUPERVISOR, DISTRICT I	DATE