

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

BLM Roswell District

Modified Form No.

NM60-3160-4

5. LEASE DESIGNATION AND SERIAL NO.

NM 19421

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Catterson SS Federal

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

Pecos Slope Abo

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Unit E, Sec. 7-T7S-R26E

12. COUNTY OR PARISH

Chaves

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different depth.
Use "APPLICATION FOR PERMIT—" for such proposals.)

SEP 21 89

1. OIL WELL ☐ GAS WELL ☒ OTHER

O. C. D.

2. NAME OF OPERATOR

YATES PETROLEUM CORPORATION

3a. AREA CODE & PHONE NO.

505/748-1471

3. ADDRESS OF OPERATOR

105 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

1980' FNL & 660' FWL, Sec. 7-7S-26E

14. PERMIT NO.

API #30-005-62721

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3704.5' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)

Spudded 26" hole 2:45 PM 9-5-89 with Frank's Rathole Service. Set 46' of 20" conductor. Notified James Brasfield, BLM, Roswell, NM, of spud. Resumed drilling 14-3/4" hole 4:45 PM 9-6-89. Notified Vic Coats, BLM, Roswell, NM. Ran 22 joints 10-3/4" 40.5# J-55 casing set 953'. Guide shoe set 953', insert float set 907'. Cemented w/500 sx Halliburton Lite w/10#/sx Gilsonite + 1/2#/sx Flocele + 3% CaCl2 (yield 2.12, wt 12.2). Tailed in w/200 sx Class C + 2% CaCl2 (yield 1.32, wt. 14.6). PD 1:00 PM 9-8-89. Bumped plug to 650 psi, released pressure and float held okay. Cement did not circulate. WOC 26 hrs and 45 minutes. NU and tested to 2000 psi for 15 minutes, OK. Reduced hole to 7-7/8". Resumed drilling.

9/15/89

Phone call to Tim Bessel:
Was cmt. behind 10 3/4" casing brought to surface?

Tim said "yes", as follows:

Temp. survey -> TOC at 177'.

One inch W/ 300+K. C.C + 3% CaCl2

TOC = 77'

One inch to surface W/ 50+K.

Peter W Chester

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Production Supvr.

DATE 9-13-89

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD
PETER W. CHESTER
DATE

SEP 15 1989

BUREAU OF LAND MANAGEMENT
ROSWELL RESOURCE AREA

*See Instructions on Reverse Side