

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

FEB 26 '90

WELL API NO.

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

LG 6319

7. Lease Name or Unit Agreement Name

Yates "36" State

8. Well No.

2

9. Pool name or Wildcat

Wildcat

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

2. Name of Operator

BHP Petroleum Company Inc. ✓

3. Address of Operator

5847 San Felipe Ste 3600 Houston TX 77057-3005

4. Well Location

Unit Letter L : 1980 Feet From The South Line and 890 Feet From The West Line

Section 36 Township 10S Range 26E NMPM Chaves County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3706.6 GL

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Drilling History ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.)

SEE BLUE 1103
The subject well was spud @ 8:00 AM on 10/13/89. Drilled 12 1/4" hole to 440' KB. Ran 10 jts 8 5/8" 24# ST&C K-55 casing, set @ 436'. Cmt w/250 sx "C" w/2% CaCl₂ 1/4# Celloflake. Circulate 50 sx to surface. WOC 10 hours. Drilled to 2400'. Ran GR-CCL-CBL-logs. Ran 58 jts 4 1/2" J-55 10.5# ST&C csg (2419'), 8 centralizers over btm 16 jts, set @ 2406'. Cmt w/200 sx "C" lite w/2% A-7, tail in w/250 sx "C" with 1/4 pps Celloflake. Pump plug w/38 bbls 2% KCL water. Circ cmt. Rig released @ 7:00 pm on 10/20/89. MIRU. Weld on bell nipple. Install WH, BOP. RIH w/73 jts 2 3/8". Tag @ 2360'. Pull up to 1757'. Spot 100 gal 15% acetic acid @ 1757-1630'. Run Gr-CCL-CBL from 2359-1500'. Perf w/ 3 1/8" csg gun w/2 SPF @ 1700-46', (93 holes). RIH w/ 50 jts 2 3/8" J-55 tbq. Set pkr @ 1626'. Acidize w/5000 gal 15% NEFE. Well TA'd.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Chris Camden TITLE Senior Petroleum Engr. DATE 2/21/90

TYPE OR PRINT NAME Chris Camden (713) 780-5000 TELEPHONE NO.

(This space for State Use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: