

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
Artesia, NM 88210

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

ckf

SUNDRY NOTICES AND REPORTS ON WELLS RECEIVED

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		JAN 11 '90	
2. NAME OF OPERATOR YATES PETROLEUM CORPORATION		(505) 748-1471 C. D.	
3. ADDRESS OF OPERATOR 105 South 4th St., Artesia, NM 88210		ARTESIA, OFFICE	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 330' FSL & 1980' FWL, Sec. 28-T6S-R25E		5. LEASE DESIGNATION AND SERIAL NO NM-11593	
14. PERMIT NO. 30-005-62748		15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3741.9' GR	
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data		6. IF INDIAN, ALLOTTEE OR TRIBE NAME N/A	
NOTICE OF INTENTION TO:		7. UNIT AGREEMENT NAME N/A	
TEST WATER SHUT-OFF <input type="checkbox"/>		8. FARM OR LEASE NAME Red Rock NB Federal	
FRACTURE TREAT <input type="checkbox"/>		9. WELL NO. 2	
SHOOT OR ACIDIZE <input type="checkbox"/>		10. FIELD AND POOL, OR WILDCAT Pecos Slope Abo	
REPAIR WELL <input type="checkbox"/>		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Unit N, Sec. 28-6S-25E	
(Other) <input type="checkbox"/>		12. COUNTY OR PARISH Chaves	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*		13. STATE NM	

12-12-89. Lost circulation at 1130'. Spotted LCM pill, no results.
Ran 35 joints 8-5/8" 24# J-55 ST&C casing set 1522'. Guide shoe set 1522', insert float set 1478'. Cemented w/150 sx Class C w/12.5% Thixad, 1/2# Celloseal and 10# Hyseal, 300 sx Pacesetter Lite w/1/2# Celloseal, 10# Hyseal and 3% CaCl₂ (yield 1.84, wt, 12.7). Followed w/200 sx Class C w/2% CaCl (yield 1.32, wt 14.8). PD 11:00 PM 12-13-89. Bumped plug to 750 psi, float held okay. Cement did not circulate. WOC 6 hrs. Ran Temp. Survey and found TOC 1000'. Ran 1". Tagged cement 1047'. Spotted 75 sx Class C w/6% CaCl. PD 2:45 PM 12-14-89. WOC 4-1/2 hrs. Ran 1". Tagged cement 970'. Spotted 400 sx Class C Neat. PD 9:30 PM 12-14-89. Circulated 10 sx. WOC 39 hrs and 45 minutes. Drilled out 2:45 PM 12-15-89. NU and tested to 1000 psi for 30 minutes, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature]

TITLE Production Supervisor

DATE 12-20-89

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

ACCEPTED FOR RECORD
PETER W. CHESTER
DATE _____

JAN 8 1990

BUREAU OF LAND MANAGEMENT
ROSWELL RESOURCE AREA

*See Instructions on Reverse Side