

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

FEB - 9 1990

WELL API NO. 30-005-62757
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. LG 4926

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	7. Lease Name or Unit Agreement Name East Wind State Unit
2. Name of Operator YATES PETROLEUM CORPORATION	8. Well No. 2
3. Address of Operator 105 South 4th St., Artesia, NM 88210	9. Pool name or Wildcat Wildcat Ordovician
4. Well Location Unit Letter J : 1980 Feet From The South Line and 1980 Feet From The East Line Section 28 Township 9S Range 27E NMPM Chaves County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3845' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 12 1/4" hole 10:30 AM 2-3-90 with Frank's Rat Hole. Drilled to 40'. Notified NMOC, Artesia, NM of spud. Resumed drilling 5:45 PM 2-4-90. Ran 21 joints 8-5/8" 24# J-55 ST&C casing, set 922'. Guide shoe set 922', insert float 878'. Cemented w/ 500 sx Lite w/1/5# Flocel, 5# Gilsonite and 2% CaCl2 (yield 1.84, wt 12.7). Followed w/ 150 sx Class C w/2% CaCl2 (yield 1.32, wt 14.8). PD 3:00 AM 2-6-90. Bumped plug to 500 psi, float held okay. Cement circulated 30 sacks. WOC. Cement fell back. Redi-mix to surface w/2 yards, 6 sx mix cement. NU and tested to 1000 psi for 30 minutes. Drilled out 9:30 PM 2-6-90. WOC 18 hrs and 30 minutes. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Mike Williams TITLE Production Supervisor DATE 2-8-90
TYPE OR PRINT NAME _____ TELEPHONE NO. _____

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS
SUPERVISOR, DISTRICT II

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

FEB 12 1990