

Submit 3 Copies
to Appropriate
District Office

BLM	<input checked="" type="checkbox"/>
Land Office	<input checked="" type="checkbox"/>
B of M	<input checked="" type="checkbox"/>
Operator	<input checked="" type="checkbox"/>

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-005-62761
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V 1362
7. Lease Name or Unit Agreement Name VALLEY B 27 STATE
8. Well No. #1
9. Pool name or Wildcat BROWN QUEEN GRAYBURG

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
Oil Well ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator

DEANS, INC.

3. Address of Operator

PO BOX 457, ARTESIA, NM 88210

4. Well Location

Unit Letter H : 2310 Feet From The NORTH Line and 660 Feet From The EAST Line

Section 27

Township 10 SOUTH Range 26 EAST

NMPM

CHAVES County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3702.0 GROUND LEVEL

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1) Spud Well 1/31/90 @ 3:30 PM with 8 3/4" Bit.

2) T.D. Well 2/7/90 @ 830 Feet.

3) 2/8/90 Ran 26 Jts. 830 Ft. 5 1/2" 17# LT&C and ST&C J-55 Csg. Top of shoe Jt. @ 821 Ft. cement with 335 sacks class C cement with 1/4 # flocele per sack. Circulate 10 sacks to pit. Plug down 11:58 2/8/90

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE

DATE

TYPE OR PRINT NAME

TELEPHONE NO.

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS
SUPERVISOR, DISTRICT II

TITLE

DATE

FEB 2 1990

CONDITIONS OF APPROVAL, IF ANY: