

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

clsf
dp

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-005-62779
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. LG 5246
7. Lease Name or Unit Agreement Name Pathfinder AFT State
8. Well No. 8
9. Pool name or Wildcat Diablo San Andres
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3833' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210

4. Well Location Unit Letter G : 2310 Feet From The North Line and 2239 Feet From The East Line Section 21 Township 10S Range 27E NMPM Chaves County
--

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6-8-90. Ran 13 joints 8-5/8" 24# J-55 ST&C casing, set at 535'. Guide shoe set 530'. Insert float set 488'. Cemented w/250 sx Class C w/1/2# Celloseal, 10# Gilsonite + 2% CaCl2 (yield 1.32, wt. 14.8). Tailed in w/200 sx Class C + 2% CaCl2 (yield 1.32, wt 14.8). PD 2:30 PM 6-8-90. Bumped plug to 400 psi, float did not hold. Bumped plug 3 times, float would not hold. SI with 400 psi. Cement circulated 47 sacks. WOC. Drilled out 2:30 PM 6-9-90. WOC 24 hrs. NU and tested, held okay. Reduced hole to 8". NU and began drilling.

6-18-90. Drilling 1020' - Anhydrite and Sand.

6-21-90. TD 1140' sand.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 6-26-90
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS
SUPERVISOR, DISTRICT II

APPROVED BY _____ TITLE _____ DATE JUN 28 1990

CONDITIONS OF APPROVAL, IF ANY: