

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

SEP 05 '90

WELL API NO.

30-005-62794

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

L-794

7. Lease Name or Unit Agreement Name

Hanlad State

8. Well No.

1

9. Pool name or Wildcat

Diablo

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR REDRILL A WELL IN A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

2. Name of Operator

Stevens Operating Corporation

3. Address of Operator

P. O. Box 2408, Roswell, New Mexico 88202

4. Well Location

Unit Letter K : 1980 Feet From The South Line and 2310 Feet From The West Line

Section 16

Township 10S

Range 27E

NMPM Chaves

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3889 GR, 3901 KB

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

August 10, 1990 Rig up Frank's Rat Hole Service, spud @1:25 a.m. 08/10/90. Drilled 40' of 20" surface hole, ran 40'/16" surface Csg., sealed in w/2 1/2 yards Ready Mix.

August 12, 1990 L & M Rig #1 - Rig up, commenced drilling 5:00 p.m.

August 13, 1990 Ran 25 Jts 10 3/4" 40.6# Csg, set @1006', Cmt. w/100 sxs thick set class "C" cmt., 1/2# flo seal, 10# gilsonite, 3%CaCl2 + 450 sxs halite, 1/2# flo seal, 10# gilsonite and 2% CaCl2 and tail in w/250 sxs class "C" cmt., 2% CaCl2. Plug down 5:00 a.m. 08/14/90. Cmt. did not circulate to surface.

August 14, 1990 Ran 1" pipe & Cmt. w/225 sxs class "C" cmt., 2% CaCl2 1 1/2 hrs, WOC 18 hrs., Pressure up 1000# for 30 min. logging no pressure decrease.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Robert C. Farmer

TITLE

Production Supt.

DATE

Sept. 4, 1990

TYPE OR PRINT NAME

TELEPHONE NO. 505-622-7273

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS
SUPERVISOR, DISTRICT II

APPROVED BY

TITLE

DATE

SEP 11 1990

CONDITIONS OF APPROVAL, IF ANY: