District I PO Box 1980, Hobbs, NM 88241-1980 District II PO Drawer DD, Artesia, NM 88211-0719 District III 1000 Rio Brazos Rd., Aztoc, NM 87410 District IV PO Box 2088, Santa Pe, NM 87504-2088 APPLICATION FOR PE			719 (D	State of New Mexico Energy, Minerals & Natural Resources Department OIL CONSERVATION DIVISION PO Box 2088 Santa Fe, NM 87504-2088 RMIT TO DRILL, RE-ENTER, DEEPEN, P.					Form C-101 V Revised February 10, 1994 Instructions on back Submit to Appropriate District Office State Lease - 6 Copies Fee Lease - 5 Copies AMENDED REPORT			
~			YATES 105 S	PETROI outh Fo	LEUM CORPO	RATION		RECA	SIW.	• • •	5575	
⁴ Prop	erty Code		ALCES.	La, New		88210 Property Name hfinder A		<u>111N2</u>	3 1997		VT Number 05-62795 • Well No.	
							url st	atte CO	uNi fi	$\mathcal{M}^{\mathcal{U}}$	9 .	
UL or lot so.	Section	Townshi	ip Range	Lot Ida	Surface	Location	<u> </u>		ਤ ਹਾਟ ਇ	ខែមេជីភ	······································	
N	21	10S	27E		Feet from the 660 '	South		Feet from the 2200 '	Exil/Wo Wes		Cocaty Chaves	
UL or lot no.	Section	Township	roposed	Bottom	Hole Loca	tion If Dif	ferent	From Sur	face		L	
ĸ	21			Lot Ida	Feet from the	North/South	line	Feet from the	East/We	t line	Comment	
	21	10S	27E		1520'	South		2600'	Wes		Consty	
Diabl	0 Files	Prop Alman	omed Pool I Associa				<u>_</u>	" Propos			Chaves	
" Work Type Code E " Multiple			u Well Type Code O		" Cable/Rotary R		" Lease Type Code S		ie	" Ground Level Elevation 3822 ' GR		
No		T M	" Proposed Depth TVD 6350' MD 7250'		"Formation Fusselman		" Contractor Unknown			³⁴ Spud Date ASAP		
			21	Propose	d Casing a	nd Cement	Prog					
Hole Size		Casi	Casing Size Casin		g weight/foot Setting De		epth Sacks of Cement					
14 3/4"			3/4"	40.5#		997'-In place				Estimated TOC		
9 1/2"		7 :	3/8"	26.4# & 27.9#		6410'-In place		1825 sx		Circulated		
		Open	Open hole					None None		Circulated		
								none		ļ		
)escribe the pro	posed prog	raus. If th	application	in to DEEP								
SEE ATTA	E Die would p	AGE 2	program, if an	99. Use add LLING P	EN or PLUG BAC	EVE Gala Xessary.	on the pr		ted - 7-			
creby certify the	t the inform	Lation sive	above is to the									
hereby certify that the information given above is true and complete to the best by knowledge and belief. manure: M_{R} , M_{M}						Approved by: SUPERVISOR, DISTRICT II						
C1	ifton	R. May	<u> </u>		Title	:						
Regulatory Agent						Approval Date: JUL 1 C 1997 Expiration Date 1 0 1998						
June 2.	5, 199	/	(505)	748-14		ched D						

Page 2

PROPOSED DRILLING PROGRAM FOR THE PATHFINDER "AFT" STATE #9

Yates Petroleum Corporation proposes to enter this existing wellbore and set a whipstock plug and directionally drill this well. Kickoff point will be at 6135' MD; build angle of 28.65 degrees/100', the angle at the end of build being 90 degrees, the point of penetration into the Fussleman being at a point 136' from the wellbore and a lateral length in the payzone of 864' (1000' total horizontal displacement). 90.0 degrees at 6540.5' MD and 6349.9' TVD with TD being a 7250.8 MD and 6350.0' TVD. (See Exhibit #2). Will kickoff with a 6 3/4" bit and complete the well open hole.

MUD PROGRAM: Cut Brine to TD.

BOPE PROGRAM: BOPE will be installed on the 8 5/8" casing and tested daily for operational.