CONTACT RECEIVING BLM Roswell District NM Oil Cons. "nmmission OFFICE FOR NUMBER Modified form No. OF OPIES REQUIRE Drawer DUNI7_J STATES NM060-3160-4 (July 1989) (Formerly 9-331) DERARIMENT 89 51 THE INTERIOR verse alde) 5. LEASE DESIGNATION AND SERIAL NO. NM 11593 BUREAU OF LAND MANAGEMENT 6. IF INDIAN, ALLOTTEE OR TRIBE NAME SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals.) 7. UNIT AGREEMENT NAME GAR WELL O'HER W E1.1. 8. FARM OR LEASE NAME 2. NAME OF OPERATOR Area Code & Phone No. 505/748-1471 Red Rock NB Federal YATES PETROLEUM CORPORATION 9. WELL NO. 3. ADDRESS OF OPERATOR RECEIVED 105 South 4th St., Artesia, NM 88210 LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) 10. FIELD AND POOL, OR WILDCAT Pecos Slope Abo NOV 26 '90 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 660' FNL & 1980' FWL, Sec. 28-6S-25E O. C. D. Unit C, Sec. 28-T6S-R25E 15. RIEVATIONS (Show whether DF, RT, GR, etc.) ARTESIA, OFFICE 12. COUNTY OR PARISH | 13. STATE 14. PERMIT NO. 3816' GR Chaves 30-005-62796 Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data 16. REPAIRING WELL WATER SHUT-OFF PULL OR ALTER CASING TEST WATER SHUT-OFF PRACTURE TREATMENT PRACTURE TREAT SHOUTING OR ACIDIZING ABANDON MENT SHOOT OR ACIDIZA ABANDON REPAIR WELL (Norm: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) (Other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and mensured and true vertical depths for all markers and zones pertinent to this work.) Spudded 26" hole 3:30 PM 10-27-90 with rathole. Set 40' of 20" conductor. Notified Junior Hogwood with BLM of spud. Resumed drilling 17½" hole 3:45 PM 10-28-90. Ran 16 joints 13-3/8" 54.5# J-55 ST&C casing set 673'. Guide shoe set 673', insert float set 630'. Cemented w/350 sx "C" Lite, w/3% CaCl, 1/4#/sx Celloseal, (yield 1.98, wt 12.4). Tailed in w/200 sx "C" w/2%CaCl (yield 1.32, wt 14.8). PD 10:05 AM 10-30-90. Bumped plug to 900 psi, released pressure, float held okay. Circulated 220 sx cement. WOC. Drilled out 6:05 AM 10-31-90. WOC 18 hrs. Cut off and weld on flow nipple. Reduced hole to 12-1/4". Drilled float and cement and resumed drilling. 18. I hereby certify that the foregoing is true and correct THILE Production Supervisor DATE 11-12-90 ACCEPTED FOR RECORD This space for Federal or State office use; PELER W. CHESTE APPROVED BY CONDITIONS OF APPROVAL, IF ANY: NOV 21 1990 *See Instructions on Reverse Side BUREAU OF AND MANAGEMENT Title 13 U.S.C. Section 1981, makes it a crime for any person knowingly and willfully to make to any department or agency of the