

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

RECEIVED

NOV - 1 1990

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. LH-2962

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name NA
12. Name of Operator Slash Four Enterprises, Inc. ✓	8. Farm or Lease Name Mashed "O" State
13. Address of Operator P.O. Box 1433, Roswell, N.M. 88202-1433	9. Well No. 1
14. Location of Well UNIT LETTER K 2310 FEET FROM THE South LINE AND 1650 FEET FROM THE West LINE, SECTION 35 TOWNSHIP 11S RANGE 27E NMPM.	10. Field and Pool, or Wildcat Wildcat, S.A.
15. Elevation (Show whether DF, RT, GR, etc.) 3774.6 GR	12. County Chaves

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103.

Commenced drilling operations September 29, 1990 and drilled a 12 1/4" hole to 149'. Encountered fresh water from 133-37'. Ran 10 3/4" pipe and mudded in to shut off water.

Drilled a 10" hole to 500'. Encountered salt water at 341-50 and 359-62', encountered sulfur water at 359-62'.

Pulled 10 3/4" pipe out of hole and ran 500' of 8 5/8" 24# casing with insert float and guide shoe. Cemented casing with 200 sx of premium plus cement with 2% CaCl. Pumped plug to float and pressured up to 600 psi and held 30 minutes. Had good returns throughout job but cement did not circulate. W.O.C. 48 hours and found top of cement at 30' from surface. Filled annulus with cement.

Commenced drilling 8" hole on October 31, 1990.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE President DATE 10/31/90

APPROVED BY ORIGINAL SIGNED BY MIKE WILLIAMS SUPERVISOR, DISTRICT II TITLE DATE NOV 6 1990
CONDITIONS OF APPROVAL, IF ANY: