Submit 3 Copies to Appropriate District Office

State of New Mexico Energy, Minerals and Natural Resources Department

Form	C	-10	3
Revis	ed	1-1	-89

DISTRICT! OIL CONSERVATION DIVISION WELL API NO.			
P.O. Box 1980, Hobbs, NM 88240 P.O. Box 2088 30-005-62822			
DISTRICT II P.O. Drawer DD, Artesia, NM 88210 Santa Fe, New Mexico 87504-2088 5. Indicate Type of Lea	STATE FEE X		
DISTRICT III 1000 Rio Brazos Rd., Aziec, NM 87410 6. State Oil & Gas Lea	se No.		
SUNDRY NOTICES AND REPORTS ON WELLS			
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 7. Lease Name or Unit	Agreement Name		
I. Type of Well: OIL WELL ONE WELL OTHER			
2. Name of Operator YATES PETROLEUM CORPORATION 8. Well No. 2			
3. Address of Operator O. C. D. 9. Pool name or Wildow	1		
105 South 4th St., Artesia, NM 88210 ARTESIA, CFFICE Wildcat Ordo	vician		
4. Well Location Unit Letter G: 1980 Feet From The North Line and 2310 Feet From The	East Line		
Section 29 Township 9S Range 26E NMPM Cha	ves County		
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3761' GR			
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Da	ıta		
NOTICE OF INTENTION TO: SUBSEQUENT REP	PORT OF:		
PERFORM REMEDIAL WORK			
TEMPORARILY ABANDON CHANGE PLANS COMMENCE BRILLING OF NO.			
PULL OR ALTER CASING CASING TEST AND CEMENT JOB X	CASING TEST AND CEMENT JOB X		
OTHER: OTHER:			
12. Describe Proposed or Completed Operations (Clearly state all perinent details, and give perinent dates, including estimated date of state work) SEE RULE 1103. Spudded 26" hole 4:50 PM 7-2-91. Notified Mike Williams, NMOCD, Artesia, Set 53' of 20" conductor. Cmt'd w/150 sx "C" + 2% CaCl2. Circulated 25 Encountered river gravel at 35'. Hit water at 39'. Drilled to firm format Resumed drilling 14-3/4" hole 8:15 AM 7-5-91. Notified Mike Williams, NMOC Ran 23 joints 9-5/8" 36# J-55 ST&C casing set 1013'. Guide shoe set 1013's set 969'. Cmt'd w/550 sx Halliburton Lite with 5# Gilsonite + 1/4# Flocel 1.84, wt 12.8). Tail in w/200 sx "C" with 2% CaCl2 (yield 1.32, wt 14.8). 7-6-91. Bumped plug to 600 psi, float held okay. Circulated 15 sacks to out 3:30 AM 7-7-91. WOC 14 hrs. NU and tested to 1000 psi for 30 mintues to 7-7/8" and resumed drilling. Notified Mike Williams with NMOCD - did to 1000 psi for 30 mintues to 7-7/8" and resumed drilling.	NM, of spud. sacks. Note: ation at 53'. OCD, Artesia, NM. ', insert float Le + 2% CaCl2 (yield PD 1:30 PM pit. WOC. Drilled s. Reduced hole		
Junita Coodlett			
Production Supervisor	_ DATE7-10-91 		

. , . . , . . .

CONDITIONS OF APPROVAL, IF ANY: