

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

IL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87504 JUN 06 1991

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

U. C. D.
ARTESIA OFFICE

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. B-8385-2	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator SLASH FOUR ENTERPRISES INC.	8. Farm or Lease Name MARBOB STATE
3. Address of Operator PO BOX 1433, ROSWELL, NM 88202-1433	9. Well No. 1
4. Location of Well UNIT LETTER J 1650 FEET FROM THE South LINE AND 1650 FEET FROM East LINE, SECTION 13 TOWNSHIP 11S RANGE 27E NMPM.	10. Field and Pool, or Wildcat CHISUM, S.A.
15. Elevation (Show whether DF, RT, GR, etc.) 3773 g.l.	12. County Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

Drilled an 8" hole to 2083', TD 5/11/91. Ran LTD Log and Ran 2082" of 4 1/2" used K-55 10.5# casing in hole with insert float, guide shoe and 5 centralizers. Cemented casing with 125 sx Haliburton Premium Plus cement w/ 5# salt/sx and .2% CFR-3. Pumped plug to float and pressured casing to 900 psi and held 30 minutes. Plug down @ 6:27 pm 5/23/91.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED J. Phelps White IV TITLE President DATE 06/05/91
J. PHELPS WHITE IV

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: