

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy	T. Canyon
T. Salt	T. Strawn
B. Salt	T. Atoka
T. Yates	T. Miss
T. 7 Rivers	T. Devonian
T. Queen	T. Silurian
T. Grayburg	T. Montoya
T. San Andres 1414	T. Simpson
T. Glorieta 2604	T. McKee
T. Paddock	T. Ellenburger
T. Blinney YESO 2684	T. Gr. Wash
T. Tubb	T. Delaware Sand
T. Drinkard	T. Bone Springs
T. Abo 4850	T. Ordovician - 6360
T. Wolfcamp 5526	T.
T. Penn Clastic 6211	T.
T. Cisco (Bough C) 6085	T.

Northwestern New Mexico

T. Ojo Alamo	T. Penn. "B"
T. Kirtland-Fruitland	T. Penn. "C"
T. Pictured Cliffs	T. Penn. "D"
T. Cliff House	T. Leadville
T. Menefee	T. Madison
T. Point Lookout	T. Elbert
T. Mancos	T. McCracken
T. Gallup	T. Ignacio Otzte
Base Greenhorn	T. Granite
T. Dakota	T.
T. Morrison	T.
T. Todillo	T.
T. Entrada	T.
T. Wingate	T.
T. Chinle	T.
T. Permian	T.
T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 3, from.....to.....
No. 2, from.....to.....	No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
No. 2, from.....to.....feet.....
No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0	453	453	Surface, Redbeds, Anhy				
453	995	542	Anhy				
995	1180	185	SS, Anhy				
1180	1390	210	SS, Sh				
1390	1950	560	Dolo, Anhy				
1950	2130	180	Dolo				
2130	2490	360	LS				
2490	2620	130	Dolo, Anhy				
2620	2940	320	Sd, Dolo, Anhy, Salt				
2940	3210	270	Dolo, Anhy, Salt				
3210	3530	320	Dolo, Anhy				
3530	3810	280	Dolo, Anhy, Salt				
3810	4050	240	Dolo, Anhy				
4050	4300	250	Dolo, Anhy, Salt				
4300	4880	580	Dolo, Anhy				
4800	5200	320	Sh				
5200	5570	370	Sh, Dolo, Anhy				
5570	6350	780	LS, Sh				
6350	6460	110	Dolo, Cht				
6460	6750	290	Dolo, Sh, Cht				