NW 011 Cons. Commission
wer DD
Artesia, NW 88210

Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

Expires: March 31, 1993

5. Lease Designation and Serial No.

NM 19421 SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well Oil Well Well 8 Well Name and No. 2. Name of Operator Catterson SS Federal #5 (505) 748-1471 9. API Well No. YATES PETROLEUM CORPORATION 3. Address and Telephone No. 30-005-62833 10. Field and Pool, or Exploratory Area 105 South 4th St., Artesia, NM 88210 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Pecos Slope Abo 11. County or Parish, State Unit K, 1650' FSL & 1980' FWL, Sec. 7-T7S-R26E Chaves, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12 TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Change of Plans Abandonment Recompletion **New Construction** X Subsequent Report Non-Routine Fracturing Plugging Back Water Shut-Off Casing Repair Final Abandonment Notice Conversion to Injection Altering Casing Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spudded 26" hole 9:45 AM 12-9-92. Set 40' of 20" conductor. Circulated cement to surface

Spudded 26" hole 9:45 AM 12-9-92. Set 40' of 20" conductor. Circulated cement to surface with redi-mix. Resumed drilling 14-3/4" hole 5:30 PM 12-10-92. Ran 23 joints 10-3/4" 40.5# J-55 ST&C casing set 1010'. Guide shoe set 1010'. Float collar set 966'. Cemented w/425 sx PSL "C" + 3% CaCl + 1#/sx Celloseal (yield 1.85, wt 12.7). Tailed in w/200 sx "C" + 2% CaCl2 (yield 1.32, wt 14.8). PD 5:35 PM 12-12-92. Bumped plug to 500 psi, float held okay. Circulated 85 sacks. WOC. Drilled out 5:45 AM 5-13-92. WOC 12 hrs and 10 mins. NU and tested to 1000 psi for 30 minutes, OK. Reduced hole to 7-7/8" and resumed drilling. NOTE: Notified BLM, Roswell, NM to witness - did not witness.

Signal Landa Dondlett	Title Production Supervisor ACCEPTED TO 25 Date 12-16-92			
	Title _PTOQUE	ction supervise	L 1. 4 (1) (1)	
This space for Federal or State office use)			CHESTER	•
Approved by	Title		Date	1
Conditions of approval, if any:	•		FEB 11 :993	Ì
	·	į		<u> </u>
tle 18 U.S.C. Section 1001, makes it a crime for any person knowing representations as to any matter within its jurisdiction.	ngly and willfully to mal	te to any department or agend	ODthe United States any false, fictition	s or fraudulent state