

ASF

Form 3160-5  
(June 1990)

RECEIVED

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

5. Lease Designation and Serial No.  
NM 19421

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Catterson SS Federal #5

9. API Well No.

30-005-62833

10. Field and Pool, or Exploratory Area

Pecos Slope Abo

11. County or Parish, State

Chaves, NM

SUBMIT IN TRIPLICATE

RECEIVED

FEB 18 1993

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit K, 1650' FSL & 1980' FWL, Sec. 7-T7S-R26E

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Ran production casing, perforate, treat


- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

TD 4300'. Reached TD 12-17-92. Ran 96 joints 4-1/2" 10.5# J-55 ST&C casing set 4300'. Float shoe set 4300', float collar set 4255'. Cemented w/425 sx Super "C" + 5% Salt, .35% CF-2 + 8#/sx Hiseal (yield 1.73, wt 12.6). PD 5:45 PM 12-18-92. Bumped plug to 1250 psi for 30 minutes, float and casing held okay. WOC 18 hours.\*\*  
Perforated 3688-3862' w/20 - .42" holes (1 SPF) as follows: 3688, 89, 90, 94, 95, 96, 3709, 10, 11, 12, 13, 14, 15, 3845' 46, 58, 59, 60, 61 and 3862'. Straddled perms 3845-62' and acidized w/1000g. 7 1/2% NEFE acid. Straddled perms 3688-3715' and acidized w/1000g. 7 1/2% NEFE. Frac'd perms 3688-3862' w/50000g. 30# linear gel + 100000# 20/40 sand.

\*\*Ran 1600' of 1". Cemented w/300 sacks 65/35/6.



14. I hereby certify that the foregoing is true and correct

Signed Marita Doadlitz

Title Production Supervisor

(This space for Federal or State office use)

Approved by \_\_\_\_\_  
Conditions of approval, if any:

Title \_\_\_\_\_

12-28-92

ACCEPTED FOR RECORD  
PETER W. CHESTER  
Date

FEB 11 1993

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side