Form 3160-5 (June 1990) UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMEN

JAN 1 3 1993

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

NM 19421
6. If Indian, Allottee or Tribe Name

			SUNDRY NOTICES AND REPORTS ON WELLS	_
Do	not	use th	his form for proposals to drill or to deepen or reenting a different lise "APPLICATION FOR PERMIT—" for such proposals	nt reserve
	,		USO "APPLICATION FOR PERMIT—" for such proposals	\$\/

NM Oil Cons. Drawer DD Artesia, N

SUBMIT	IN TRIPLICATE	- 1993 ·	7. It blint of CA, Agreement Designation
1. Type of Well  Oil  Well  Well  Other  2. Name of Operator  YATES PETROLEUM CORPORATION	(505) 748-14	O. C. D. (71)	8. Well Name and No.  Catterson SS Federal Com #6  9. API Well No.
3. Address and Telephone No.  105 South 4th St., Artesia, M.  4. Location of Well (Footage, Sec., T., R., M., or Survey De  Unit 0, 660! FSL & 1650! FEL, Se	escription)		30-005-62857  10. Field and Pool, or Exploratory Area Pecos Slope Abo  11. County or Parish, State
12. CHECK APPROPRIATE BOX(	s) TO INDICATE NATURE OF		Chaves, NM RT, OR OTHER DATA
TYPE OF SUBMISSION  Notice of Intent  Subsequent Report	Abandonment Recompletion Plugging Back	TYPE OF ACTION	Change of Plans  New Construction  Non-Routine Fracturing
Final Abandonment Notice	Casing Repair Altering Casing Other		Water Shut-Off     Conversion to Injection     Dispose Water     (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded 26" hole 11:20 AM 12-29-92. Set 40' of 20" conductor, redi-mixed to surface.

Notified Larry Bray, BLM, Roswell, NM, of spud.

Resumed drilling 14-3/4" hole 8:00 PM 1-7-93. Ran 23 joints 10-3/4" 40.5# J-55 ST&C casing set 1000'. Guide shoe set 1000', Insert float set 955'. Cemented w/450 sx PSL + 1# Hiseal, + 3% CaCl2 (yield 1.84, wt 12.8). Tailed in w/200 sx "C" + 2% CaCl2 (yield 1.32, wt 14.8). PD 9:30 PM 1-9-93. Bumped plug to 600 psi, float held OK. Circulated 117 sacks cement. WOC. Drilled out 10:00 PM 1-10-93. WOC 24 hrs, 30 minutes. Reduced hole to 7-7/8" and resumed drilling.

14. I hereby certify that the foregoing is frue and correct Signal antu and and del	Title Production Superv	isor
(This space for Federal or State office use)	September of September 1	PETER W. CHESTER
Approved by	Title	Date CHESTER
		agency of the United States any false, fictitions or fraudulent statement
Title 18 U.S.C. Section 1001, makes it a crime for any por representations as to any matter within its jurisdiction	person knowingly and willfully to make to any department of a	SURFAILOS
	*See Instruction on Reverse Side	BUREAU OF LAND MANAGEMENT



\*