NN Oil Cons. Com seion Drawer DD

Form 3160-5 (June 1990)

→ Notice of Intent

Subsequent Report

Final Abandonment Notice

## Artesia, NM 88210 UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED

NM 11593 6. If Indian, Allottee or Tribe Name

Change of Plans

**New Construction** 

Water Shut-Off

Dispose Water

Non-Routine Fracturing

Conversion to Injection

(Note: Report results of multiple completion on Well

	Bı	iaget Buri	tau No.	1004-0133
		Expires:	March	31, 1993
5.	Lease	Designat	ion and	Serial No.

<b>SUNDRY NOTICES</b>	AND	REPORTS	ON	WELLS
-----------------------	-----	---------	----	-------

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposal RECEIVED 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE <u>- 9 1992</u> I. Type of Well Oil Well Gas Well 8. Well Name and No. Other Red Rock NB Federal #6 2. Name of Operator (505) 748-1471)9. API Well No. YATES PETROLEUM CORPORATION 3. Address and Telephone No. 30-005-62858 10. Field and Pool, or Exploratory Area 105 South 4th St., Artesia, NM 88210 Pecos Slope Abo 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 11. County or Parish, State Unit B, 660' FNL & 1980' FEL, Sec. 28-T6S-R25E Eddy, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF ACTION TYPE OF SUBMISSION

Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\* TD 4100'. Reached TD 10-6-92. Ran 98 joints 4-1/2" 9.5# J-55 casing set 4100'. Float shoe

Abandonment Recompletion

Plugging Back

Casing Repair

Altering Casing

XX Other Production Casing

Perforate, Treat

set 4100', float collar set 4061'. Cemented with 575 sx 65/35 Poz "C" with 2% gel, .6% Halad-322 and 2#/sx Salt (yield 1.22, wt 14.1). PD 1:23 PM 10-7-92. Bumped plug to 1300 psi for 30 mins. Cemented 4-1/2" casing x 8-5/8" annulus thru 1" tubing from 1600' to surface with 300 sx PSL.

10-12-92. Perforated 3942-51' w/8 .42" holes as follows: 3942, 43, 44, 45, 46, 49, 50 and 3951' (1 SPF). Acidize 3942-51' w/1000g. 7½% NEFE/HCL acid. Frac'd perfs 3942-51' w/20000g. 30 # 1 = ge1 + 40000 # 20/40 sand. Perforated 3620-3740 # w/13 - .42 # holes as follows: 3620, 22, 33, 34, 35, 40, 41, 42, 46, 47, 3738, 39 and 3740' (1 SPF). Straddle perfs 3738-40' and acidize w/500g. 7½% NEFE/HCL acid. Straddle perfs 3620-47' w/1000g. 7½% NEFE/HCL acid. Frac'd perfs 3620-3740' w/20000g. 30# linear gel + 40000# 20/40 sand.

Title 18 U.S.C. Section 1001, makes it a crime for any person representations as to any matter within its jurisdiction.	on knowingly and willfully to make to any departmen	nt or agency of the United States any false, fictitious or fraudulent statem  SONNEL RESOURCE ARE  Side
Conditions of approval, if any:		NOV 18 1992
(This space for Federal or State office use)  Approved by	Title	PETER W. CHESTER Date
14. I hereby certify that the foregoing is true and correct Signed 1 anta 2 and unit	Title Production Supe	