

Form 3160-5  
June 1990)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

RECEIVED  
DEC 10 1991

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS O. C. D.  
ARTESIA OFFICE

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

CIBOLA ENERGY CORPORATION

3. Address and Telephone No.

P.O. BOX 1668 ALBUQUERQUE, NM 87103

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1650 FT FNL & 324 FT. FWL (lot 2)  
Sect 18 9-S 28-E, Chaves County, NM

5. Lease Designation and Serial No.

NM-12557

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

DUNCAN FEDERAL 4

9. API Well No.

4Y

10. Field and Pool, or Exploratory Area

WILDCAT

11. County or Parish, State

CHAVES, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent  
☐ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other CEMENT JOB

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

WELL REACHED TD AT 2308 FT ON 08/09/91

CASING: SET 53 JOINTS OF 4 1/2" 10.5 LB/FT. J-55 CASING. CASING WAS SET AT 2306 FT. FLOAT COLLAR WAS SET AT 2297 FT. SIX CENTRALIZERS WERE SET AT THE FOLLOWING DEPTHS: 2214, 2083, 1951, 1864, 1645, AND 1515 FT.

CEMENT: CASING WAS CEMENTED WITH 90 SACKS OF HALLIBURTON LITE AND 115 SACKS OF PREMIUM PLUS CEMENT. WIPER PLUG WAS LANDED WITH 650 PSIG AND FLOAT VALVE HELD. PRESSURE HELD FOR 10 MINUTES. RELEASED PRESSURE, SHUT DOWN. WOC.

14. I hereby certify that the foregoing is true and correct

Signed Peter W. Chester

Title PRODUCTION ANALYST

Date 08/30/91

(This space for Federal or State office use)

Approved by \_\_\_\_\_  
Conditions of approval, if any:

Title \_\_\_\_\_

Date \_\_\_\_\_

DEC 9 1991

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side