State of New Mexico Ene

Minerals and Natural Resources Department

Form C-103

DISTRICT I P.O. Box 1980, Hobbs, NM 88ZAD

OIL CONSERVATION DIVISION P.O. Box 2088

β		-
WELL API NO	<u>.</u>	
	5-62880-0000	

DISTRICT II				
O. Drawer DD, Artesia, NM \$8210	Santa Fe, New Mexico 87504-2088		5. Indicate Type of Lease STATEXX FEE	
STRICT III 00 Rio Brezos Rd., Aztec, NM 87410			6. State Oil & Gas Lease No.	
DO NOT USE THIS FORM FOR PROPO DIFFERENT RESERVO	S AND REPORTS ON WELLS ISALS TO DRILL OR TO DEEPEN OF BR. USE "APPLICATION FOR PERMI I) FOR SUCH PROPOSALS.)	R PLUG BACK TO A	7. Lease Name or Unit Agreement Name Desert Rose	
Type of Well:				
WELL XX	ОТНЕА			
Name of Operator McKay Oil Corporation			8. Well No.	
Address of Operator		1	9. Pool pame or Wildcat	
P. O. Box 2014, Roswe	11, NM 88202		W. Pecos Slope Abo	
	Feet From The South	Line and990	Feet From The West Line	
Section 12	Township 6S Range	. 22E N	MPM Chaves County	
	10. Elevation (Show whether DF 4094			
Check Ap	propriate Box to Indicate Na NTION TO:	iture of Notice, Rej SUBS	port, or Other Data SEQUENT REPORT OF:	
RFORM REMEDIAL WORK	PLUG AND ABANDON XX	REMEDIAL WORK	ALTERING CASING	
MPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLING	OPNS. PLUG AND ABANDONMENT	
LL OR ALTER CASING	(CASING TEST AND CEN	AENT JOB	
HER:		OTHER:	U	
work) SEE RULE 1103.			ing estimated date of starting any proposed	
McKay Oil Corporation 1. Set CIBP @ 2875' 2. Set 5 sks cement p 3. POH 4. Cut 4 1/2" @ 2750' 5. Set 25 sks cement 6. WOC - Tag plug. 7. Set 50 sks cement 8. WOC - Tag Plug 9. Set 30 sks cement 10. Install Dry hole m 11. Brine gel between McKay Oil anticipates	plans to plug and abalug 2875' to 2840', applug across 4 1/2" stuplug across 8 5/8" shoplug 100' to surface. Tarker and clean locatiall cement plugs. Noti	endon this well oprox. 35'. The second open second op	as follows:	
McKay Oil Corporation 1. Set CIBP @ 2875' 2. Set 5 sks cement p 3. POH 4. Cut 4 1/2" @ 2750' 5. Set 25 sks cement 6. WOC - Tag plug. 7. Set 50 sks cement 8. WOC - Tag Plug 9. Set 30 sks cement 10. Install Dry hole m 11. Brine gel between McKay Oil anticipates	plans to plug and abalug 2875' to 2840', applug across 4 1/2" stuplug across 8 5/8" shoplug 100' to surface. arker and clean locatiall cement plugs. Noting this well plugs of complete to the best of my knowledge and best	oprox. 35'. ub 2840' to 270 ue 1054' to 950 ion. ify NMOCD to wi	as follows: O' tness plugging operations. oned on or before February 21, 1	
McKay Oil Corporation 1. Set CIBP @ 2875' 2. Set 5 sks cement p 3. POH 4. Cut 4 1/2" @ 2750' 5. Set 25 sks cement 6. WOC - Tag plug. 7. Set 50 sks cement 8. WOC - Tag Plug 9. Set 30 sks cement 10. Install Dry hole m 11. Brine gel between McKay Oil anticipates Thereby cerufy that the information above is true as the series of the series o	plans to plug and aballug 2875' to 2840', applug across 4 1/2" stuplug across 8 5/8" shoplug 100' to surface. The larker and clean locatical cement plugs. Notice the larker by the larker and complete to the best of my knowledge and best of my kno	oprox. 35'. ub 2840' to 270 ue 1054' to 950 ion. ify NMOCD to wi	tness plugging operations. oned on or before February 21, 1	
McKay Oil Corporation 1. Set CIBP @ 2875' 2. Set 5 sks cement p 3. POH 4. Cut 4 1/2" @ 2750' 5. Set 25 sks cement 6. WOC - Tag plug. 7. Set 50 sks cement 8. WOC - Tag Plug 9. Set 30 sks cement 10. Install Dry hole m 11. Brine gel between McKay Oil anticipates I hereby certify that the information above is that a	plans to plug and aballug 2875' to 2840', applug across 4 1/2" stuplug across 8 5/8" shoplug 100' to surface. The larker and clean locatical cement plugs. Notice the larker by the larker and complete to the best of my knowledge and best of my kno	oprox. 35'. ub 2840' to 270 ue 1054' to 950 ion. ify NMOCD to wi	as follows: O' tness plugging operations. oned on or before February 21, 1	
McKay Oil Corporation 1. Set CIBP @ 2875' 2. Set 5 sks cement p 3. POH 4. Cut 4 1/2" @ 2750' 5. Set 25 sks cement 6. WOC - Tag plug. 7. Set 50 sks cement 8. WOC - Tag Plug 9. Set 30 sks cement 10. Install Dry hole of 11. Brine gel between McKay Oil anticipates **Inhartire** Bill J. Mils **TYPE OR PRINT NAME** Bill J. Mils (This space for Sialo Uso)	plans to plug and aballug 2875' to 2840', applug across 4 1/2" stuplug across 8 5/8" should be sufface. The surface arker and clean location all cement plugs. Noting this well plug accomplate to the best of my knowledge and be stead.	indon this well oprox. 35'. ub 2840' to 270 oe 1054' to 950 on. ify NMOCD to wingged and abandonia. Vice President	tness plugging operations. oned on or before February 21, 1	