

## SUPPLEMENTAL DRILLING DATA

MCKAY OIL CORPORATION  
South Four Mile Draw Federal #13  
SE/4SE/4 of Sec. 23, T-6S, R-22E  
Chaves County, New Mexico

NM-36194

The following items supplement Form 9-331C in accordance with instruction contained in NTL-6.

1. SURFACE FORMATION: San Andres
2. ESTIMATED TOPS OF GEOLOGICAL MARKERS:

Yeso	-	740'
Tubb	-	2258'
Abo	-	2948'
3. ESTIMATED DEPTHS TO WATER, OIL OR GAS FORMATION:

Fresh Water	-	In surface formation above 600'
Gas	-	In Abo formation below 2946'
4. PROPOSED CASING PROGRAM: See Form 9-331C
5. PRESSURE CONTROL EQUIPMENT: Blowout preventer will consist of at least a double-ram blowout preventer rated to 3000#WP. A sketch of the BOP is attached. *Used as 219 system*
6. CIRCULATING MEDIUM:

Air Drilling to 100' above the top of the Abo formation. Then mud-up till TD.
7. AUXILIARY EQUIPMENT: Full-opening drill string safety valve fit for the drill string in use, will be kept on the rig floor at all times.
8. TESTING, LOGGING AND CORING PROGRAM:

Samples:	Catch samples from surface to TD.
DST'S:	None
Logging:	GR-CNL, Dual Lateral MSFL from surface to TD.
Coring:	None