

+ 2157
Op

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

SEP 17 1992

WELL API NO.
30-005-62905

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
LG 4908

7. Lease Name or Unit Agreement Name

Cactus Flower State Unit

8. Well No.
3

9. Pool name or Wildcat
Wildcat San Andres

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter D : 330 Feet From The North Line and 330 Feet From The West Line
Section 16 Township 8S Range 27E NMPM Chaves County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3974' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: Surface & Production Casing ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 12-1/4" hole 9-9-92. Notified NMOC, Artesia, NM, of spud. Ran 8 joints 8-5/8" 24# J-55 casing set at 355'. Guide shoe set 355', insert float set 311'. Cemented w/250 sx "C" + 2% CaCl2 (yield 1.32, wt 14.8). PD 11:09 PM 9-9-92. Bumped plug to 800 psi, held OK. Circulated 64 sacks cement. WOC. Drilled out 7:30 PM 9-11-92. WOC 44 hrs and 21 minutes. Reduced hole to 7-7/8" and resumed drilling. TD 2200'. Reached TD 9-13-92. Ran 51 joints 5-1/2" 15.5# J-55 LT&C casing set at 2200'. Guide shoe set 2200', float collar set 2156'. Cemented w/300 sx PSL "C" + 1/4# Celloseal + 2% CaCl2 (yield 1.80, wt 12.8). Tailed in w/100 sx Class "C" + 0.5% CF-1 + 1-1/2% CaCl (yield 1.32, wt 14.8). PD 3:58 AM 9-14-92. Bumped plug to 1200 psi for 3 minutes, float and casing held. Circulated 94 sacks. WOC 24 hrs.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 9-16-92

TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS

APPROVED BY SUPERVISOR, DISTRICT II TITLE DATE SEP 18 1992

CONDITIONS OF APPROVAL, IF ANY: