

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

WELL API NO.

30-005-62906

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

VA-2058

7. Lease Name or Unit Agreement Name:

Aviator AVO State

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 S. 4th Street Artesia, NM 88210

7. Well No.

#1

8. Pool name or Wildcat

Wildcat Precambrian

4. Well Location

Unit Letter E : 1980 feet from the North line and 990 feet from the West line

Section 33 Township 9S Range 27E NMPM Chaves County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3891' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Spud re-entry. Set production casing. ☒


Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

5/11/01 - Spud re-entry. Drill cement from 15-65'.

5/12 - 5/23/01 - Drill cement plugs, wash and clean out to TD at 6505'.

5/24/01 - Ran 150 joints 5-1/2" 15.5# J55 casing set at 6493'. Float shoe set at 6493'. Float collar set at 6454'. Cemented with 200 sxs BJ Lite + 6% gel + 3# salt and 300 sxs Super C modified 15:61:11 + .4% FL52 + .4% FL25 + 2# salt.

5/25/01 - PD at 1:00AM. WOC.



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Susan Herpin TITLE Engineering Technician DATE January 14, 2002

Type or print name Susan Herpin

Telephone No. 505-748-1471

(This space for State use)

APPROVED BY [Signature] ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR

Conditions of approval, if any: _____

DATE _____

JAN 28 2002