

CLSF

Form 3160-5  
(June 1990)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

**RECEIVED**

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1471

O. C. D.

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit G, 1650' FNL & 1650' FEL, Sec. 27-T7S-R25E

5. Lease Designation and Serial No.  
NM 17202

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Short RM Federal Com #4

9. API Well No.

30-005-62909

10. Field and Pool, or Exploratory Area

Pecos Slope Abo

11. County or Parish, State

Chaves, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☐ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☒ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded 26" hole 9:00 AM 10-12-92. Set 40' of 20" conductor. Redi-Mix to surface.  
Resumed drilling 17 1/2" hole 4:30 PM 10-13-92. Lost circulation at 670'. TD 17 1/2" hole 10:30 AM 10-15-92. Ran 20 jts 13-3/8" 54.5# J-55 casing set 855'. Guide shoe set 855', insert float set 812'. Cemented w/500 sx Lite w/1/2#/sx Flocele, 3#/sx Granulite, 3% CaCl2 (yield 1.84, wt 12.7). Tail in w/200 sx Neat w/2% CaCl2 (yield 1.32, wt 14.8). PD 6:00 PM 10-15-92. Bumped plug to 400 psi, float held okay. Cement did not circulate. WOC 4 hrs. Ran 7 stages of 1". Cmt'd with 300 sx "C" Neat. Circulated 2 sacks. PD 3:00PM 10-16-92. WOC. Drilled out 8:30 PM 10-16-92. WOC 26 hrs and 30 mins. Cut off and weld on flow nipple. Reduced hole to 12 1/2" and resumed drilling. Notified BLM Answering Service, Roswell, NM - not witnessed. TD 12 1/2" hole 6:00 PM 10-17-92. Ran 35 jts 8-5/8" 24# J-55 casing set 1455'. Guide shoe set 1455', float collar set 1410'. Cemented w/350 sx H/L w/3#/sx Granulite, 1/3#/sx Flocele, 3% CaCl2 (yield 1.84, wt 12.8). Tail in w/200 sx "C" w/2% CaCl2 (yield 1.32, wt 14.8). PD 1:00 AM 10-18-92. Bumped plug to 600 psi, float held OK. Cement did not circulate. WOC. Drilled out 6:00 PM 10-18-92. WOC 17 hours. NU and tested to 1000 psi for 30 minutes, OK. Reduced hole to 7-7/8". Notified BLM, Roswell, NM - not witnessed.

14. I hereby certify that the foregoing is true and correct

Signed Peter W. Chester

Title Production Supervisor

Date 10-20-92

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date

NOV 18 1992

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side