

CSF
1

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

OCT 19 1992

O. C. D.
ARTESIA OFFICE

WELL API NO. 30-005-62911
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. VB-427
7. Lease Name or Unit Agreement Name Hanlad AKZ State
8. Well No. 2
9. Pool name or Wildcat Wildcat Ordivician
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3943' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER
2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210
4. Well Location Unit Letter M : 330 Feet From The South Line and 1225 Feet From The West Line Section 13 Township 8S Range 27E NMPM Chaves County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 17-1/2" hole 9:00 AM 10-5-92. Ran 9 joints 13-3/8" 54.5# J-55 casing set 371'. Guide shoe set 371', insert float set 331'. Cemented w/350 sx "C" with 2% CaCl2 and 1/4#/sx Celloseal (yield 1.33, wt 14.8). PD 11:30 PM 10-5-92. Bumped plug to 250 psi, held OK. Circulated 65 sacks. WOC. *Press test 1000* Drilled out 1:45 PM 9-6-92. WOC 14 hours and 15 minutes. Cut off and weld on flow nipple. Resumed drilling 12-1/4" hole. NOTE: Notified NMOC, Artesia, NM, did not witness. TD 12-1/4" hole 2:45 PM 10-8-92. Ran 39 joints 8-5/8" 24# J-55 casing set 1630'. Guide shoe set 1630', Float collar set 1588'. Cemented w/550 sx PSL "C" with 5#/Salt + 1/4#/sx Celloseal (yield 1.98, wt 12.5). Tailed in w/200 sx "C" with 2% CaCl2 (yield 1.32, wt 14.5). PD 8:00 PM 10-8-92. Bumped plug to 900 psi, float held OK. Cement did not circulate. WOC. Drilled out 2:00 PM 10-9-92. WOC 18 hours. Reduced hole to 7-7/8" and resumed drilling. *Press Test 1000*

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 10-12-92

TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS
SUPERVISOR, DISTRICT II

APPROVED BY _____ TITLE _____ DATE OCT 22 1992

CONDITIONS OF APPROVAL, IF ANY: