

# OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO.  
30-005-62911

5. Indicate Type of Lease  
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.  
VB-427

7. Lease Name or Unit Agreement Name  
Hanlad AKZ State

8. Well No.  
2

9. Pool name or Wildcat  
Paloma Mesa

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT (FORM C-101) FOR SUCH PROPOSALS.)

Type of Well:  
Oil Well ☐ Gas Well ☒ Other ☐

Name of Operator  
YATES PETROLEUM CORPORATION

Address of Operator  
105 South Fourth Street - Artesia, NM 88210

OCT 05 '94

Well Location  
Unit Letter M : 330 Feet From The South Line and 1225 Feet From The West Line

Section 13 Township 8S Range 27E NMPM Chaves County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)  
3943' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: Acid <input checked="" type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9-28-94 - Dropped down with 2-7/8" tubing and reverse 18' of sand out of casing. TOOH with 2-7/8" tubing. TIH with packer and 2-7/8" tubing. Removed BOP and nipped up wellhead. Set packer at 6293'. Loaded and tested annulus to 500 psi. Swabbed. Shut in.

9-29-94 - Nipped down wellhead and installed BOP. Unset packer. Dropped down to 6375'. Spotted 5 bbls 15% NEFE acid. Pulled packer up to 6249' and reverse 3 bbls. Set packer at 6249'. Removed BOP and nipped up wellhead. Pumped 2% KCL water down 2-7/8" tubing to put acid away. Swabbed. Rigged down swab and pumped 500 gallons 15% NEFE acid into perms. 6354-6369'. Swabbed. Shut well in.

9-30-94 - Swab and flow test. Acidized sand jet perforations 6354-6369' with 1500 gallons 15% NEFE acid. Swabbed & flowed well. Shut down.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Production Clerk DATE 10-3-94

TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505-748-1471

(This space for State Use)

SUPERVISOR, DISTRICT II

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE OCT 5 1994