

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

cliff  
up

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

RECEIVED

NOV 20 1992

O. C. D.

WELL API NO.

30-005-62920

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

LG 4334

7. Lease Name or Unit Agreement Name

Sparrow SP State

8. Well No.

3

9. Pool name or Wildcat

Pecos Slope Abo

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL  
WELL ☐

GAS  
WELL ☒

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South 4th St., Artesia, NM 88210

4. Well Location

Unit Letter M : 660 Feet From The South Line and 660 Feet From The West Line

Section 32 Township 6S Range 25E NMPM Chaves County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3968' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 12:30 PM 11-9-92. Set 40' of 20" conductor pipe. Cement to surface with 2 yards of redi-mix. Resumed drilling 17 1/2" hole 3:30 PM 11-11-92. Ran 17 joints 13-3/8" 54.5# J-55 ST&C casing set at 748'. Guide shoe set 748'. Insert float set 702'. Cemented w/525 sx H/L with 1# Flocele + 3% CaCl2 (yield 1.84, wt 12.7). Tail in w/200 sx Premium Plus "C" w/2% CaCl2 (yield 1.32, wt 14.8). PD 7:10 AM 11-13-92. Bump plug to 450 psi, float held OK. Circulated 83 sacks. WOC. Drilled out 9:45 PM 11-13-92. WOC 14 hrs and 35 mins. Cut off and weld on flow nipple. Reduced hole and resumed drilling. Notified Mike Williams, NMOCD, Artesia, NM, did not witness.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Juanita Goodlett

TITLE Production Supervisor

DATE 11-17-92

TYPE OR PRINT NAME

TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY

MIKE WILLIAMS

SUPERVISOR, DISTRICT II

APPROVED BY

TITLE

DATE

NOV 25 1992

CONDITIONS OF APPROVAL, IF ANY: