

+ c15f
Op

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

DEC 16 1992

O.C.D.
OFFICE

WELL API NO.
30-005-62922

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Ric

8. Well No.

8

9. Pool name or Wildcat

Pecos Slope Abo

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☒

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South 4th St., Artesia, NM 88210

4. Well Location

Unit Letter K : 1980 Feet From The South Line and 1980 Feet From The West Line

Section 20

Township 6S

Range 25E

NMPM

Chaves

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3821' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Ran production casing, perforate, trt ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 4000'. Reached TD 12-6-92. Ran 90 joints 4-1/2" 10.5# J-55 ST&C casing set 4000'. Float shoe set 4000', float collar set 3955'. Cemented w/350 sx Super "C" w/8#/sx Hiseal, 5% Salt, and .3% CF-2 (yield 1.76, wt 13). PD 1:00 PM 12-7-92. Cement did not circulate. Bumped plug to 1200 psi for 10 mins, held OK. WOC 24 hrs. Perforated 3546-3553' w/8 holes (1 SPF) and 3514-3521' w/8 holes (1 SPF). Acidized 3546-53' w/1000g. 7 1/2% NEFE. Acidized 3514-21' w/1000g. 7 1/2% NEFE. Frac'd all perf's 3514-53' w/40000g 30# linear gel w/80000# 20/40 Brady sand.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett

TITLE Production Supervisor

DATE 12-15-92

TYPE OR PRINT NAME

Juanita Goodlett

TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY

MIKE WILLIAMS

DEC 30 1992

APPROVED BY SUPERVISOR DISTRICT II

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: