Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR

1a.,:	NM PORM APPROVED
ŀ	Budget Bureau No. 1004-0135
	Expires: March 31, 1993

BUREAU IF L	5. Lease Designation and Serial No.		
SINDDA MUMULES	NM-14755		
SUNDRY HODICES . Do not use this form for process to dri	6. If Indian, Allottee or Tribe Name		
Use "APPLICATION FOR	R PERMIT—" for such proposals	иг.	
	To duty proposals		
SUBMIT	IN TRIPLICATE	7. If Unit or CA, Agreement Designation	
1. Type of Well	The state of the s		
Oil G Gas		0. W.1.V.	
2. Name of Operator	8. Well Name and No. Powers OL Federal #8		
YATES PETROLEUM CORPORATION	9. API Well No.		
3. Address and Telephone No.	30-005-62923		
105 South 4th St., Artesia, N	10. Field and Pool, or Exploratory Area		
4. Location of Well (Footage, Sec., T., R., M., or Survey De	Pecos Slope Abo		
Unit J, 1980' FSL, 1980' FEL, S	11. County or Parish, State		
UNITE 0, 1900 IBE, 1900 IEE, 1	Charre - M		
		Chaves, NM	
12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REF	PORT, OR OTHER DATA	
TYPE OF SUBMISSION			
TITE OF SUBMISSION	TYPE OF ACTION	ON	
Notice of Intent	Abandonment	Change of Plans	
(F)	Recompletion	New Construction	
X Subsequent Report	Plugging Back	Non-Routine Fracturing	
Π	Casing Repair	Water Shut-Off	
Final Abandonment Notice	Altering Casing	Conversion to Injection	
	LX Other <u>Set Surface Casing</u>		
13. Describe Beaucod of Completed Co	Set Production Casing	Completion of Personalistics Parasit and Landau	
give subsurface locations and measured and true vertica	pertinent details, and give pertinent dates, including estimated date of stall depths for all markers and zones pertinent to this work.)*	arting any proposed work. If well is directionally drilled,	
Spudded 26" hole 7:10 AM 11-18-9	92. Set 40' of 20" conductor. Cem	ented to surface. Resumed	
drilling 17-1/2" hole 4:00 PM 1	1-19-92. Ran 16 joints 13-3/8" 54.	5# J-55 ST&C casing set	
650'. Guide shoe set 650', inse	ert float set 610 . Cemented $w/350$	sx PSL "C" w/3% CaC12 + 1#	
Celloseal (yield 1.85, wt 12.7). Tailed in w/200 sx "C" w/2% CaCl2 (yield 1.32, wt 14.8).			
PD 9:26 PM 11-21-92. Bumped plu	ng to 700 psi, float held OK. Circu	lated 145 sacks cement. WOC	
Drilled out 9:30 AM 11-23-92. T	WOC 36 hours. Cut off and well on	flow nipple. Reduced hole	
to 7-7/8" and resumed drilling	NOTE: Notified BLM, Roswell, NM	, did not witness.	
Float show set (250) float self	Ran 100 joints 4-1/2" 10.5# J-55	ST&C casing set 4250'.	
Salt + 37 CF-2 DD 1.75 DM 11-4	lar set 4206'. Cemented w/325 sx S	uper "C" w/5# Hyseal + 5%	
held OK. WOCU 24 hours.	28-92. Bumped plug to 750 psi for	15 mins. Float and casing	
note on. wood 24 hours.			
	1、1年1日 1月1日 - 1		
,一个"我们"的"我们","我们的"我们"的"我们"的"我们"的"我们"的"我们"的"我们"的"我们"的"			
14. I hereby certify that the foregoing is true and correct			
Signal anta Doodless	Title Production Supervisor		
	The rioudction Supervisor	ACCEPTED FOR 12-1-92	
(This space-for Federal or State office use)		ETER W. CHESTER	
Approved by	Title	Date	
		DEC	
		DEC 11 1992	

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agending the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

ROSWELL RESOURCE