	DEPAL MENT OF BUREAU OF LAND SUNDRY NOTICES AND	MANAGEMENT	Artesia, NM 8	
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.				6. If Indian, Allottee or Tribe Name
SUBMIT Type of Well	'IN TRIPLICATE-C	Other instructions on	reverse side	7. If Unit or CA/Agreement, Name and/or No.
X Oil Well Gas Well	Other			8. Well Name and No.
Name of Operator				DANA FEDERAL #7
GOT	HIC PRODUCTION CORF	ORATION		9. API Well No.
a. Address 6120 S. YALE, STE 1200 TULSA, OK 74136 . Location of Well (Footage, Sec., T., R., M., or Survey Description) . Location of Well (Footage, Sec., T., R., M., or Survey Description)				30-005-62924
				10. Field and Pool, or Exploratory Area S. PECOS SLOPE ABO
	-	приол)		11. County or Parish, State
660 FNL & 2330 FEL, SEC. 9-T9S-R25E				CHAVES, NM
12. CHECK /	APPROPRIATE BOX(F	S) TO INDICATE NAT	TURE OF NOTICE, REPO	
TYPE OF SUBMISSION				NI, OK OTHEK DATA
			TYPE OF ACTION	
Notice of Intent	Acidize	Deepen	Production (Start/Resume)	Water Shut-Off
	Alter Casing	Fracture Treat	Reclamation	Well Integrity
Subsequent Report	Casing Repair	New Construction	Recomplete	Other
Final Abandonment Notice	Change Plans	X Plug and Abandon	Temporarily Abandon	
	Convert to Injection	Plug Back	Water Disposal	
in property were subsequenties	ords shall be filed within 30 days follo a completed. Final Abandonment Not P&A OPERATIONS CMT ON CIBP	owing completion of the involved oper	rations. If the operation results in a multip rements, including recamation, have been c	work will be performed or provide the Bond No. on file the completion or recompletional at it interval. a Form completed, and the performance interval and the performance interval interval at its site is SEF 2030 EF 2030 CD - ARTESIA OCD - ARTESIA
/30/00 IRC HOLE WITH MUD LAD OLID CMT PLUG FROM 950 UT OFF 4.5 AND 8 5/8 WELI	EN FLUID, PUMP 160 SX 'TO SURF INSIDE AND C	CMT FROM 3000' TO 2850 DUT OF 4.5., PUMPED 125	Approved Liability	t as to plugging of the well bors, under bond is retained until
/30/00 CIRC HOLE WITH MUD LAD OLID CMT PLUG FROM 950 CUT OFF 4.5 AND 8 5/8 WELI	EN FLUID, PUMP 160 SX 'TO SURF INSIDE AND C	DUT OF 4.5., PUMPED 125	<b>Approve</b> Liability	as to plugging of the well bors, under bond is retained until restoration is completed.
Add 4.5 Constraints (30/00) (30/00) CRC HOLE WITH MUD LAD OLID CMT PLUG FROM 950 UT OFF 4.5 AND 8 5/8 WELI ILL IN WORKOVER PIT. hereby certily that the foregoing is to mane (Printed/Typed	EN FLUID, PUMP 160 SX ' TO SURF INSIDE AND C L HEADS.	DUT OF 4.5., PUMPED 125	Approved Liability	t as to plugging of the well bors, under bond is retained until
/30/00 IRC HOLE WITH MUD LAD OLID CMT PLUG FROM 950 UT OFF 4.5 AND 8 5/8 WELI ILL IN WORKOVER PIT. hereby certily that the foregoing is tr ame (Printed/Typed JUCE HANEY	EN FLUID, PUMP 160 SX ' TO SURF INSIDE AND C L HEADS.	DUT OF 4.5., PUMPED 125	<b>Approve</b> Liability	t as to plugging of the well bors, under bond is retained until
/30/00 IRC HOLE WITH MUD LAD OLID CMT PLUG FROM 950 UT OFF 4.5 AND 8 5/8 WELI ILL IN WORKOVER PIT.	EN FLUID, PUMP 160 SX ' TO SURF INSIDE AND C L HEADS.	DUT OF 4.5., PUMPED 125	Approved Liability surface	t as to plugging of the well bors, under bond is retained until
/30/00 IRC HOLE WITH MUD LAD OLID CMT PLUG FROM 950 UT OFF 4.5 AND 8 5/8 WELI ILL IN WORKOVER PIT. hereby certily that the foregoing is tr ame (Printed/Typed JUCE HANEY	EN FLUID, PUMP 160 SX 'TO SURF INSIDE AND C HEADS, ue and correct THIS SPACE	DUT OF 4.5., PUMPED 125	Approved Liability surface	t as to plugging of the well bors, under bond is retained until
/30/00 IRC HOLE WITH MUD LAD OLID CMT PLUG FROM 950 JUT OFF 4.5 AND 8 5/8 WELL ILL IN WORKOVER PIT. hereby cettly that the foregoing is tr ame (Printed/Typed JUEE HANEY Institute Mathematical States of the second states of the seco	EN FLUID, PUMP 160 SX TO SURF INSIDE AND C HEADS.	DUT OF 4.5., PUMPED 125	Approved Liability surface DUCTION ANALYST	as to plugging of the well born, under bond is retained until restoration is completed.
/30/00 IRC HOLE WITH MUD LAD OLID CMT PLUG FROM 950 UT OFF 4.5 AND 8 5/8 WELI ILL IN WORKOVER PIT.	EN FLUID, PUMP 160 SX TO SURF INSIDE AND C HEADS. ue and correct THIS SPACE	Title PROD Date 9-6-00 FOR FEDERAL OR	Approved Liability surface	t as to plugging of the well born, under bond is retained until restoration is completed.

• 1

Ξ.

i

3