

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

RECEIVED

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

O. C. D.
WELL NO. 30-005-62927
5. Indicate Type of Lease
STATE ☒ FEE ☐
6. State Oil & Gas Lease No.
LG-3591
7. Lease Name or Unit Agreement Name
Tamarack QF State Com
8. Well No.
3
9. Pool name or Wildcat
Pecos Slope Abo

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER ☐
2. Name of Operator
YATES PETROLEUM CORPORATION
3. Address of Operator
105 South 4th St., Artesia, NM 88210
4. Well Location
Unit Letter E : 1650 Feet From The North Line and 660 Feet From The West Line
Section 32 Township 6S Range 26E NMPM Chaves County
10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3654' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO:
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐
SUBSEQUENT REPORT OF:
REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 1:40 PM 12-30-92. Set 58' of 20" conductor. Cemented w/115 sacks C w/2% CaCl2. Circulated 64 sacks. Notified Carmen, NMOCD, Artesia, NM of spud. Resumed drilling 12-1/4" hole 1-6-93. Lost circulation at 725'. Ran 23 joints 8-5/8" 24# J-55 ST&C casing set at 945'. Guide shoe set 945', insert float set 901'. Cemented w/300 sx H/L w/1# Flocele + 2% CaCl2 (yield 1.84, wt 12.8). Tailed in w/200' sx Premium Plus with 2% CaCl2 (yield 1.32, wt 14.8). PD 1:30 PM 1-6-93. Bumped plug to 100 psi, float held OK. Cement did not circulate. WOC 7 hours. Ran Temperature Survey and found TOC at 700'. Ran 23 stages of 1" and cemented w/980 sx Premium Plus + 3% CaCl2 + 120 yards gravel. Circulated 5 sacks to pit. WOC. Plug down on last stage 12:00 NOON 1-8-93. Drilled out 9:30 PM 1-9-93. WOC 80 hours. Cut off and weld on flow nipple. Reduced hole to 7-7/8" and resumed drilling.

Note: Witnessed by Gary Williams and Mike Stubblefield, NMOCD, Artesia, NM.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 1-12-93
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS
SUPERVISOR, DISTRICT I

APPROVED BY _____ TITLE _____ DATE JAN 18 1993

CONDITIONS OF APPROVAL, IF ANY: