

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

+c15f  
D

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-005-62931

3. Indicate Type of Lease

STATE ☐

FEE ☒

State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL  
WELL ☐

GAS  
WELL ☒

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South 4th St., Artesia, NM 88210

4. Well Location

Unit Letter H : 1650 Feet From The North Line and 660 Feet From The East Line

Section 17

Township 10S

Range 25E

NMPM

Chaves

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3520' GR

7. Lease Name or Unit Agreement Name

Cannon XF

8. Well No.

1

9. Pool name or Wildcat

Pecos Slope Abo

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Surface Casing ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Resumed drilling 12-1/4" hole 11:30 AM 12-21-92. TD'd 4:00 AM 12-23-92 at 496'. Reamed hole size from 12 1/4" to 17 1/2" at 465'. Ran 3 joints 13-3/8" 54.5# K-55 ST&C set at 111'. Guide shoe set 111', insert float at 68'. Cemented w/400 sx "C" w/4% CaCl2 (yield 1.32, wt 14.8). PD 11:00 AM 12-24-92. Bumped plug to 300 psi. WOC 4 hrs. Ran 2 stages of 1" and cemented w/ 275 sx "C" + 4% CaCl2. Circulated 5 sacks. WOC. Cut off and weld on flow nipple. Drilled cut 5:00 PM 12-27-92. WOC 78 hours. NOTE: Verbal approval given by Mike Williams, NMOCD, Artesia, NM, for above procedure.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE Production Supervisor

DATE 12-30-92

TYPE OR PRINT NAME

Juanita Goodlett

TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY  
MIKE WILLIAMS

SUPERVISOR, DISTRICT II

APPROVED BY

TITLE

DATE

JAN 12 1993

CONDITIONS OF APPROVAL, IF ANY: