

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

RECEIVED

JAN 04 1993

WELL API NO. 30-005-62931
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Cannon XF
8. Well No. 1
9. Pool name or Wildcat Pecos Slope Abo
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3520' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER
2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210
4. Well Location Unit Letter H : 1650 Feet From The North Line and 660 Feet From The East Line Section 17 Township 10S Range 25E NMMPM Chaves County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3520' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Intermediate Casing <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 17 1/2" hole 6:00 PM 12-28-92. Ran 9 joints 9-5/8" 36# J-55 ST&C casing set 378'. Guide shoe set 378', float collar set 334'. Cemented w/400 sx H/L w/2.6# Granulite + 1#/sx Flocele + 2% CaCl2 (yield 1.84, wt 12.8). Tailed in w/150 sx "C" Neat + 2% CaCl2 (yield 1.32, wt 14.8). PD 4:00 AM 12-29-92. Bumped plug to 775 psi, float held OK. Cement did not circulate. Note: Witnessed by Mike Stubblefield with NMOC, Artesia, NM. Cemented 1" w/35 sx "C" Neat. Temperature Survey showed cement 70-160'. WOC. Drilled out 12:05 AM 12-30-92. WOC 20 hours and 5 minutes. Cut off and weld on flow nipple. Reduced hole to 8-3/4" and resumed drilling.

Returned -
Jana Test

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 12-30-92
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: