

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1900 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-005-62931

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Cannon XF

8. Well No.

1

9. Pool name or Wildcat

Pecos Slope Abo

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☒

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South 4th St., Artesia, NM 88210

4. Well Location

Unit Letter H : 1650 Feet From The North Line and 660 Feet From The East Line

Section 17 Township 10S Range 25E NMPM Chaves County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3520' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PLUG OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Production Casing, Perforate, Treat ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 4250'. Reached TD 1-11-93. Ran 96 joints 4-1/2" 10.5# and 11.6# J-55 and N-80 casing set 4250'. Float shoe set 4250', float collar set 4204'. DV tool set 1502'. Cemented in 2 stages. Stage I - 150 sx "C" w/8# Silicalite w/.8% Halad 322, .3% CFR-14, 1/4# Flocele, 2% KCL (yield 1.54, wt 13.0). PD 12:45 AM 1-13-93. Bumped plug to 1150 psi for 5 mins. Cement did not circulate. Circulated thru DV tool for 3-1/4 hrs. Stage II: 175 sx "C" w/2% CaCl2 (yield 1.32, wt 14.8). PD 4:45 AM 1-13-93. Bumped plug to 2350 psi for 3 mins. Circulated 25 sacks cement. Notified NMOC, Artesia, did not witness. WOC 18 hrs. Perforated Abo as follows: Zone 1) 3911, 13 and 3916' (3 holes), acidized 3911-16' w/300g. 7 1/2% NEFE. Zone 2) 3814-23' (10 holes-1 SPF); Zone 3) 3702, 3703' (2 holes); Zone 4) 3600, 01, 02, 03, 04 (5 holes). Acidized 3814-23' w/1000g. 7 1/2% NEFE. Acidized 3702-03' w/200g. 7 1/2% NEFE. Acidized 3600-04' w/400g. 7 1/2% NEFE. Frac'd all perforations 3600-3916' w/60000g. 30# Linear gel with 120000# 20/40 Brady sand.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE Production Supervisor

DATE 1-19-93

TYPE OR PRINT NAME

Juanita Goodlett

TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY

WILLIAM

APPROVED BY

SUPERVISOR DISTRICT

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

JAN 29 1993